



| Cenio mounted cultivator                          |         | Cenio 3000<br>Special/Super                                    | Cenio 3500<br>Special/Super | Cenio 4000-2<br>Special/Super |
|---------------------------------------------------|---------|----------------------------------------------------------------|-----------------------------|-------------------------------|
| Working width (m)                                 |         | 3.00                                                           | 3.50                        | 4.00                          |
| Execution                                         |         | rigid                                                          |                             | folding                       |
| Transport width (m)                               |         | 3.00                                                           | 3.50                        | 3.00                          |
| Transport length with road lights (m)             |         | 3.60                                                           |                             | 4.80                          |
| Weight (kg)<br>(Base machine, simplest execution) | Special | 1,325                                                          | 1,445                       | 2,585                         |
|                                                   | Super   | 1,515                                                          | 1,675                       | 2,895                         |
| Linkage                                           |         | 3-point linkage mounted (Cat. 3/3N)                            |                             |                               |
| No. of tines                                      |         | 10                                                             | 12                          | 13                            |
| Tine execution                                    | Special | C-Mix Special tines with shear bolt overload safety protection |                             |                               |
|                                                   | Super   | C-Mix Super tines with pressure spring overload protection     |                             |                               |
| Number of stagger                                 |         | 3                                                              |                             |                               |
| Tine spacing: tine element (cm)                   |         | 30                                                             |                             |                               |
| Frame height (cm)                                 |         | 75                                                             |                             |                               |
| Working depth: tine element (cm)                  |         | 5–30                                                           |                             |                               |
| Operational speed (km/h)                          |         | 8–15                                                           |                             |                               |
| Power requirement from (kW/hp)                    |         | 75/105                                                         | 90/125                      | 130/175                       |
| No. of d/a tractor spool valves                   |         | 0/1                                                            |                             | 2                             |

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



**AMAZONEN-WERKE H. DREYER SE & Co. KG**

P. O. Box 51 · 49202 Hasbergen-Gaste/Germany

Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193