

DH25/35 SERIES DISC HARROWS

40-100 HP | Cat. 1 & 2, Pull-Type



Hobby to Organic; Farming that is.

Land Pride DH25 and DH35 Disc Harrows offer reliable, quality conventional tillage for hobby farmers to organic operations. Available in 6', 8', 10', and 12' widths, Land Pride Disc Harrows are one of the most effective methods for mechanically eliminating weeds while leveling rutted fields.

- Tubular frame instead of angle iron
- Self aligning, sealed ball bearings
- Front and rear leveling
- Optional furrow fillers, disc scrapers, center sweep, SMV Kit, and Tongue Jack
- Disc scrapers are available to reduce build-up on discs



DH35: Heavy-duty 5/8" thick bearing hangers resist the high torque from two 3/4" U-bolts.

	DH2572	DH2596	DH3510	DH3512
Horsepower	40-100 HP		45-100 HP	55-100 HP
Hitch	Cat. 1 & 2		Pull-type Hitch with Clevis	
Working Width (cm)	72" (183)	96" (244)	10'6" (320)	12' (366)
Weight - lb (kg)	947 (430)	1,143 (518)	2491 (1,130)	2,747 (1,246)
Disc Blade Size - Diameter	20" or 22"		Front: 22" Rear: 20" or 22"	
No. of Disc Blades	20	24	28 or 32	32 or 36
Disc Blade Spacing	7-1/2"		9"	
Bearing Hanger	1/2" Plate, 2 Each 5/8" U-bolts		5/8" Plate, 2 Each 3/4" U-bolts	
Bearing Type	Self Aligning, Sealed Bearings 2 per Gang		Self Aligning Bearings 3 to 4 Bearings per Gang	
Front Gang Angling	0, 7, 14, 21 Degrees		Front: 15, 18, 21 Degrees	
Rear Gang Angling	7, 14, 21 Degrees		12, 15, 18 Degrees	
Frame Tubes	3" Square		3" x 5"	
Gang Tubes	4" x 3"		3" x 5" x 1/4" Wall Tubing	
Gang Axle	1-1/8" Square, High Carbon Steel		1-1/8" Square, High Carbon Steel	
Weight per Disc - lb (kg) 7-1/2" Spacing	47 (21)	48 (22)	79-84 (36-38)	76-82 (34-37)
Weight per Disc (kg) 9" Spacing	51 (23)	52 (24)	87-93 (39-42)	81-86 (37-39)
Transport Tires	N/A		2 Std. 9.5Lx15, 4 Optional	
Center Sweep Option	9" Sweep		9" Sweep	
Disc Scrapers	Optional, Adjustable		Optional, Adjustable	
Transport Lights	N/A		N/A	Standard
Colors				