

Product Specifications For 289D3



Engine

Gross Power - SAE J1995	74.3 hp
Net Power - SAE 1349	72.9 hp
Displacement	203 in ³
Bore	3.7 in
Stroke	4.7 in
Net Power	72.9 hp
Note	Net power advertised is the power available at the flywheel when the engine is equipped with alternator, air cleaner, muffler/aftertreatment and cooling fan.
Engine Model	Cat C3.3B DIT (turbo)
Peak Torque - 1,500 rpm - SAE J1995	195 ft·lbf
Net Power - ISO 9249	73.7 hp

Operating Specifications

Rated Operating Capacities - 35% Tipping Load	2890 lb
Tipping Load	8255 lb
Breakout Force - Tilt Cylinder	7291 lb

Rated Operating Capacity with Optional Counterweight	4370 lb
---	---------

Rated Operating Capacities - 50% Tipping Load	4130 lb
--	---------

Ground Pressure - With 450 mm/17.7 in Track	4.7 psi
--	---------

Ground Contact Area - With 450 mm/17.7 in Track	2272 in ²
--	----------------------

Note	Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 2036 mm (80 in) low profile bucket, 450 mm (17.7 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).
-------------	--

Weights

Operating Weight	10688 lb
-------------------------	----------

Note	Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 2036 mm (80 in) low profile bucket, 450 mm (17.7 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).
-------------	--

Service Refill Capacities

Cooling System	3.7 gal (US)
-----------------------	--------------

Engine Crankcase	3 gal (US)
-------------------------	------------

Fuel Tank	27.7 gal (US)
------------------	---------------

Hydraulic System	13.7 gal (US)
-------------------------	---------------

Hydraulic Tank

10.3 gal (US)

Dimensions

Length - Track on Ground 64.2 in

Overall Length - Track 83.8 in

Height - Top of Cab 83.2 in

Ground Clearance 8.9 in

Departure Angle 33°

Maximum Dump Angle 51°

Clearance at Maximum Lift and Dump 94 in

Turning Radius from Center - Machine Rear 70.7 in

Length - Without Bucket 117.9 in

Maximum Reach - With Arms Parallel to Ground 50 in

Turning Radius from Center - Bucket 88.8 in

Bucket Pin Height - Carry Position 7.5 in

Turning Radius from Center - Coupler 55.5 in

Bucket Pin Height - Maximum Lift 125.1 in

Reach - Maximum Lift/Dump 30 in

Length - With Bucket on Ground 146.2 in

Maximum Overall Height 158.1 in

Rack Back Angle - Maximum Height 84°

Bucket Pin Reach - Maximum Lift 14.5 in

Vehicle Width (450 mm/17.7 in tracks) 78 in

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 2036 mm (80 in) low profile bucket, 450 mm (17.7 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Cab

ROPS ISO 3471:2008

FOPS ISO 3449:2005 Level I

Hydraulic System

Hydraulic Flow - Standard - Hydraulic Power (Calculated) 44 hp

Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Pressure 4061 psi

Hydraulic Flow - Standard - Loader Hydraulic Flow 23 psi

Hydraulic Flow - High Flow XPS - Hydraulic Power (Calculated) 76 hp

Hydraulic Flow - Standard - Loader Hydraulic Pressure 3335 psi

Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Flow 32 gal/min

Power Train

Travel Speed - Forward or Reverse - Two Speed 8.3 mile/h

Travel Speed - Forward or Reverse - One Speed 4.5 mile/h

Air Conditioning System (If Equipped)

Air Conditioning The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1 kg of refrigerant which has a CO2 equivalent of 1.430 metric tonnes.

Noise Level

Note (2) **The declared dynamic operator sound pressure levels per ISO 6396:2008. The measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.

Outside Cab*** 103 dB(A)

Inside Cab** 83 dB(A)

Note (3) ***The labeled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC.

Note (1) Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.

289D3 Standard Equipment

ELECTRICAL

12 volt Electrical System

80 ampere Alternator

Ignition Key Start/Stop Switch

Lights: Gauge Backlighting, Two Rear Tail Lights, Two Rear Halogen Working Lights, Two Adjustable Front Halogen Lights, Dome Light

Backup Alarm

Heavy Duty Battery, 850 CCA

OPERATOR ENVIRONMENT

Advanced Display with Rearview Camera: Full Color, 127 mm (5 in) LCD screen; Advanced Multi-operator Security System; On-screen Adjustments for Implement Response, Hystat Response and Creep Control

Gauges: Fuel Level, Hour Meter

Operator Warning System Indicators: Air Filter Restriction, Alternator Output, Armrest Raised/Operator Out of Seat, Engine Coolant Temperature, Engine Oil Pressure, Glow Plug Activation, Hydraulic Filter Restriction, Hydraulic Oil Temperature, Park Brake Engaged, Engine Emission System

Adjustable Vinyl Seat

Fold In Ergonomic Contoured Armrest

Control Interlock System, when operator leaves seat or armrest raised: Hydraulic System Disables, Hydrostatic Transmission Disables, Parking Brake Engages

ROPS Cab, Open, Tilt Up

FOPS, Level I

Top and Rear Windows

Floor Mat

Interior Rearview Mirror

12 volt Electric Socket

Horn

Hand (Dial) Throttle, Electronic

Adjustable Joystick Controls

Anti-theft Security System with 6-button Keypad

Storage Compartment with Netting

POWER TRAIN

Cat C3.3B, Turbo Diesel Engine, Meeting Tier 4 Final and Stage V Emission Standards

Air Cleaner, Dual Element, Radial Seal

S-O-SSM Sampling Valve, Hydraulic Oil

Filters, Cartridge-type, Hydraulic

Filters, Canister-type, Fuel and Water Separator

Radiator/Hydraulic Oil Cooler (side-by-side)

Spring Applied, Hydraulically Released, Wet Multi Disc Parking Brakes

Hydrostatic Transmission, Two Speed Travel

Suspension – Independent Torsion Axles (4)

OTHER

Engine Enclosure, Lockable

Extended Life Antifreeze, -37° C (-34° F)

Machine Tie Down Points (6)

Support, Lift Arm

Hydraulic Oil Level Sight Gauge

Radiator Coolant Level Sight Gauge
Radiator, Expansion Bottle
Cat ToughGuard™ Hose
Auxiliary, Hydraulics, Continuous Flow
Heavy Duty, Flat Faced Quick Disconnects with Integrated Pressure Release
Split D-Ring to Route Work Tool Hoses Along Side of Left Lift Arm
Electrical Outlet, Beacon
Belly Pan Cleanout
Variable Speed Demand Fan
Product Link™ PL243, Cellular

MANDATORY EQUIPMENT

Hydraulics, Standard or High Flow XPS
Quick Coupler, Mechanical or Powered
High Visibility Seat Belt, 50 mm (2 in) or 75 mm (3 in)
Steel Imbed Rubber Track – 450 mm (17.7 in)
Dual Flange Front Idler/Single Flange Rear Idler or Triple Flange Front/Rear Idlers

PERFORMANCE PACKAGES:

- Performance Package H1: Standard Flow Hydraulics (No Self Level)
- Performance Package H2: Standard Flow, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)
- Performance Package H3: High Flow XPS, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)

COMFORT PACKAGES:

- Open ROPS (C0): Static Seat (No Foot Throttle, Headliner, Heater or Door)
- Open ROPS (C1): Foot Throttle, Headliner, Cup Holder, and choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) (No Heater or Door)
- Enclosed ROPS with Heater (C2): Foot Throttle, Headliner, Heater and Defroster, Side Windows, Cup Holder, Radio Ready, choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) and Door (Glass or Polycarbonate)
- Enclosed ROPS with A/C (C3): C2 + Air Conditioner

289D3 Optional Equipment

OPTIONAL EQUIPMENT

Hand-Foot Style Controls
External Counterweights
Beacon, Rotating
Engine Block Heater – 120V
Oil, Hydraulic, Cold Operation
Paint, Custom
Heavy Duty Battery, 1,000 CCA
Product Link PL641, Cellular
Ride Control
Bluetooth® Radio with Microphone (AM/FM/Weather Band Receiver with USB and Auxiliary Input Jack)