



ULTRA-CHISEL™

Offered in ten working widths up to 45' 9", the Ultra-Chisel removes density layers up to 8" deep while mixing residue to reduce wind erosion and improve

water infiltration. Its rocking bolster system, standard on select models, enhances the chisel's ability to follow contours and maintain even depth control.



3-SECTION MODELS
6321UC, 6324UC, 6327UC,
6329UC, 6330UC, 6333UC



5-SECTION MODELS
6539UC, 6541UC,
6543UC, 6545UC

FEATURES & BENEFITS



HEAVY-DUTY CHISEL SHANKS

The Ultra-Chisel's spring-loaded shanks have 900 lbs. of trip force for consistent tillage depth. Available in 9" or 12" shank spacing.



CHOOSE YOUR CHISEL POINT

Choices include 2" straight points, 7" winged points, 3" or 4" twisted points, or 12" or 16" hard-faced sweeps. Availability is based on shank spacing.



ROCKING BOLSTER

A center-compensating rocking bolster keeps all four sets of center-frame walking tandems firmly on the ground in uneven terrain to provide excellent depth control. Standard on 6330UC up to 6545UC and optional on all smaller sizes.



FLOATING HITCH

The floating hitch allows the tractor and the machine's frame to pivot independently. All implement wheels remain on the ground to control depth, ensuring uniform and even tillage.



30" UNDERFRAME CLEARANCE

High frame height improves residue flow under the frame.



SINGLE-POINT DEPTH CONTROL

Adjust the depth across the entire width of the machine in one convenient place.

OPTIONS (see website for complete list of features & options)



3-BAR HEAVY COIL TINE ATTACHMENT

Adjustable, heavy-duty spring tines provide enhanced trash flow and the ability to fill runs.



3-BAR HEAVY COIL TINE & REEL ATTACHMENT

Rear reel firms and levels the seedbed.



5-BAR HIGH-RESIDUE SPIKE

Five rows of 14" staggered teeth break up clods and level high-residue field conditions.



HYDRAULIC ROLLING BASKET

Offers enhanced finishing capabilities that can be adjusted on-the-go.

Ultra-Chisel™	Tillage Width (9" spacing)	Transport Width	Transport Height (9" spacing)	Engine H.P. Required	Number of Shanks (9" spacing)
6321UC	21' 9"	13' 8"	10' 10"	200+	29
6324UC	24' 9"	13' 8"	12' 4"	210+	33
6327UC	27' 9"	13' 8"	13' 10"	255+	37
6329UC	29' 3"	13' 8"	14' 7"	265+	39
6330UC	30' 9"	16' 8"	13' 10"	265+	41
6333UC	33' 9"	16' 8"	15' 4"	345+	45
6539UC	38' 3"	16' 1"	13' 3"	350+	51
6541UC	39' 9"	16' 1"	13' 3"	350+	53
6543UC	42' 9"	16' 1"	13' 8"	365+	57
6545UC	45' 9"	16' 1"	13' 8"	380+	61

See GreatPlainsAg.com for complete specifications.

Specifications are subject to change without prior notification. Images may not depict current or standard production models.

ADDITIONAL STANDARD FEATURES

- Maintenance-free lift axles, gauge wheel pivots, and walking beam pivots
- Walking tandems on front center lift axles
- Walking tandem on front gauge wheels (models 6330 and 6333)
- 12.5L x 15 tires on main transport and wing wheels
- Narrow transport widths
- Rephasing lift cylinders
- Heat-treated ductile cast tongue
- LED safety lighting

GREATPLAINSAG.COM