

## Teres 200 mounted reversible plough

| Model                       | Teres 200 V                                    |      | Teres 200 VS |      |
|-----------------------------|------------------------------------------------|------|--------------|------|
|                             | No. of furrows                                 | 4    | 5            | 4    |
| Tractor power up to (kW/hp) | 147/200                                        |      |              |      |
| Interbody clearance (cm)    | 90/100                                         |      |              |      |
| Frame height (cm)           | 80/85                                          |      | 80           |      |
| Furrow width adjustment     | Hydraulic                                      |      |              |      |
| Overload protection         | Shear bolt                                     |      | Hydraulic    |      |
| Furrow width per body (cm)  | 30 – 50 or 33 – 55                             |      |              |      |
| Support wheel (dimension)   | 10/75-15, 10/75-15.3, 340/55-16 or 360/45-17.5 |      |              |      |
| Weight (kg)                 | 1760                                           | 2058 | 2000         | 2375 |

## Teres 300 mounted reversible plough

| Model                       | Teres 300                                      |      |      | Teres 300 S        |      |      | Teres 300 V        |      |      | Teres 300 VS |      |      |
|-----------------------------|------------------------------------------------|------|------|--------------------|------|------|--------------------|------|------|--------------|------|------|
|                             | No. of furrows                                 | 4    | 5    | 6                  | 4    | 5    | 6                  | 4    | 5    | 6            | 4    | 5    |
| Tractor power up to (kW/hp) | 4 furrows: 160/220                             |      |      | 5 furrows: 190/260 |      |      | 6 furrows: 220/300 |      |      |              |      |      |
| Interbody clearance (cm)    | 100                                            |      |      |                    |      |      | 90 or 100          |      |      |              |      |      |
| Frame height (cm)           | 80/85                                          |      |      | 80                 |      |      | 80/85              |      |      | 80           |      |      |
| Furrow width adjustment     | Mechanical                                     |      |      |                    |      |      | Hydraulic          |      |      |              |      |      |
| Overload protection         | Shear bolt                                     |      |      | Hydraulic          |      |      | Shear bolt         |      |      | Hydraulic    |      |      |
| Furrow width per body (cm)  | 35/40/45/50                                    |      |      |                    |      |      | 30 – 50 or 33 – 55 |      |      |              |      |      |
| Support wheel (dimension)   | 10/75-15, 10/75-15.3, 340/55-16 or 360/45-17.5 |      |      |                    |      |      |                    |      |      |              |      |      |
| Weight (kg)                 | 1853                                           | 2140 | 2509 | 2123               | 2481 | 2920 | 1884               | 2248 | 2616 | 2211         | 2622 | 3028 |