

**SP2060, SP2072, SP3072 & SP3084**

	SP2060	SP2072	SP3072	SP3084
<b>Working Width</b>	60" (152 cm)	72" (183 cm)		84" (213 cm)
<b>Overall Width</b>	65 1/4" (166 cm)	77 1/4" (196 cm)		89 1/4" (227 cm)
<b>Weight (With Single Roller)</b>	491 lb (223 kg)	561 (255 kg)	671 (304 kg)	721 (327 kg)
<b>Max Engine Hp.</b>	35 hp (26 kW)	35 hp (26 kW)	50 hp (37 kW)	50 hp (37 kW)
<b>Number Of Shanks</b>	21	25	25	29
<b>Number Of Spikes - Single Roller</b>	86	103	103	116
<b>Number Of Spikes - Double Roller</b>	N/A	N/A	206	232
<b>Height</b>	36 1/2"		36 1/2"	
<b>Front To Back Length Single Roller</b>	25 1/2" (65 cm)		28 1/4" (72 cm)	
<b>Front To Back Length Double Roller</b>	N/A		35 1/4"	
<b>Shank Spacing</b>	2 13/16" (7 cm)		2 13/16" (7 cm)	
<b>Spiked Roller Tube Diameter</b>	5 9/16" (14 cm) O.D.		6 5/8" (17 cm) O.D. Optional Second Roller 5 9/16"(14 cm)	
<b>H-Beam</b>	10" (25.4 cm)		12" (30.5 cm)	
<b>A-Frame</b>	3/8" Plate			
<b>Springs-Front Roller</b>	32 lbs./inch (5.71 kg/cm)		32 lbs./inch (5.71 kg/cm)	
<b>Springs - Rear Roller</b>	N/A	N/A	15 lbs./inch (2.67 kg/cm)	
<b>Spike Material</b>	3/8" x 1 1/4" Steel, Replaceable Heat Treated Sleeves		3/8" x 1 1/4" Steel, Replaceable Heat Treated Sleeves	
<b>Hitch</b>	Cat. 1 Fits Land Pride Quick Hitch		Cat. 1 Fits Land Pride Quick Hitch	

35031

