

Appendix A - Reference Information

Specifications and Capacities: 3P500 and 3P600

Drill Model	3P500		3P600	
Row Count	7	9	9	11
Row Spacing	7.5 in (19.1 cm)	6.0 in (15.2 cm)	7.5 in (19.1 cm)	6.0 in (15.2 cm)
Swath	52.5 in (133.4 cm)		67.5 in (171.5 cm)	
Transport Width (w/o Lights)	59.3 in (151 cm)		74.1 in (188 cm)	
Length	67 in (145 cm)			
Working Heights	61 in (155 cm)			
Weights, Maximum, Empty	1170 lbs (530 kg)	1370 lbs (620 kg)	1466 lbs (665 kg)	1586 lbs (720 kg)
Weight, Maximum, Full	1840 lbs (840 kg)	2040 lbs (930 kg)	2270 lbs (1030 kg)	2390 lbs (1090 kg)
Main Seed Box Capacity	10 bu. (350 liters)		12 bu. (420 liters)	
Small Seeds Box Capacity	1.2 bu. (42 liters)		1.44 bu. (51 liters)	
Seed Box Agitator	Optional in Main Seed box			
Min. Tractor HP Req.	35 hp (26 kW)		40 hp (30 kW)	
Hitch Type	Category I & II			
Tire Size	5.70L X 8 Lug Type			
Operating Depth	0 to 3.5 in (0 to 8.9 cm)			

Specifications and Capacities: 3P500V

Drill Model	3P500V
Row Count	9
Row Spacing	6.0 in (15.2 cm)
Swath	54.0 in (137.2 cm)
Transport Width (w/o Lights)	58 in (146 cm)
Length	57 in (145 cm)
Working Heights	50 in (127 cm)
Weights, Maximum, Empty	1300 lbs (590 kg)
Weight, Maximum, Full	1810 lbs (230 kg)
Main Seed Box Capacity	8.5 bu (300 liters)
Seed Box Agitator	Standard
Min. Tractor HP Req.	35 hp (26 kW)
Hitch Type	Category I & II
Tire Size	5.70L X 8 Lug Type
Operating Depth	0 to 3.5 in (0 to 8.9 cm)