

## Appendix A - Reference Information

### Specifications and Capacities

<b>3P806NT</b>	
Row Spacing	7.5 in (19.1 cm)
Rows per drill	13
Swath	97.5 in (247.7 cm)
Weight, pounds	4054-4500 lbs (1839-2041 kg) <sup>a</sup>
Transport Width	approx. 99 in (251 cm)
Height	approx. 95 in (2.41 m)
Length	approx. 141 in (3.56 m)
Transport Clearance	approx. 16 in (40.6 cm) <sup>b</sup>
Capacities:	
Main Seed Box	16 bu (564 liters)
Dual Seed Box	8 bu (282 liters)
Native Grass Box	8 bu (282 liters)
Small Seeds Box	1.9 bu (67 liters)
Fertilizer Box	7.4 cubic feet (211 liters)
Agitators	Optional in Main Seed Box Standard in optional Dual Seed box. Standard in optional Native Grass box.
Transport/Lift-Assist Wheel	265/70B 16.5 NHS Skid Steer
Ground Drive Wheel	5.70L x 8, 8x3.75 4-bolt rim
Tractor Requirements	Semi-Mounted 3-Point Category II hitch, 80 hp (60 kW), 1 hydraulic circuit

a. Empty weight range: see page 23 for weights of representative configurations.

b. With rear lift lock channels installed, and semi-mounted hitch elevated to drill-level.

### Tire Inflation Chart

Tire Size	Inflation	Tire Warranty Information
265/70B 16.5 NHS Skid Steer	60 psi 414 kPa	All tires are warranted by the original manufacturer of the tire. Tire warranty information is found online at the manufacturer's websites listed below. For assistance or information, contact your nearest Authorized Farm Tire Retailer.  Manufacturer    Website Firestone        www.firestoneag.com Gleason         www.gleasonwheel.com Titan             www.titan-intl.com
5.70-8 8-Ply	50 psi 345 kPa	