

Appendix A - Reference Information

Specifications and Capacities

3P1006NT	
Row Spacing	7.5 in. (19.1 cm)
Rows per drill	15
Swath	112.5 in. (285.8 cm)
Weight, pounds	4820-6388 lbs. (2187-2898 kg) ^a
Transport Width	approx. 118.25 in. (3.00 m)
Height	approx. 95 in. (2.41 m)
Length	approx. 141 in. (3.56 m)
Transport Clearance	approx. 16 in. (40.6 cm) ^b , and depends on tractor hitch
Capacities:	
Main Seed Box	25 bu. (881 liters)
Dual Seed Box	10 bu. (352 liters)
Native Grass Box	10 bu. (352 liters)
Small Seeds Box	2.4 bu. (85 liters)
Fertilizer Box	9.2 cubic feet (261 liters)
Agitators	Optional in Main Seed box. Standard in Dual Seed or Native Grass box.
Transport/Lift-Assist Wheel	265/70B 16.5 NHS Skid Steer, 6-bolt rim
Ground Drive Wheel	5.70-8 8-Ply, 4-bolt rim
Tractor Requirements	Semi-Mounted 3-point Category II hitch, 100 hp (75 kW), 1 hydraulic circuit

a. Empty weight range: see page 23 for weights of representative configurations.

b. With rear lift lock channels installed, and semi-mounted hitch elevated to drill-level.

Tire Inflation Chart

Tire Size	Inflation
265/70B 16.5 NHS Skid Steer	60 psi 414 kPa
5.70-8 8-Ply	50 psi 345 kPa

Tire Warranty Information

All tires are warranted by the original manufacturer of the tire. Tire warranty information is found online at the manufacturer's websites listed below. For assistance or information, contact your nearest Authorized Farm Tire Retailer.

Manufacturer	Website
Firestone	www.firestoneag.com
Gleason	www.gleasonwheel.com
Titan	www.titan-intl.com