

Technical data:

UX Special trailed sprayers

Model	UX 3200 Special	UX 4200 Special	UX 5200 Special
Nominal volume (l)	3,200	4,200	5,200
Tank capacity (l)	3,600	4,600	5,600
Fresh water tank (l)	320	550	550
Working width (m)	15 – 36		
Transport height (m)	Super-S2 boom: 3.25 – 3.40 Super-L2 boom: 3.35 – 3.50		
Transport length (m) with Super-S2 boom	6.25 – 6.50	6.85 – 7.30	
Transport length (m) with Super-L2 boom	6.40 – 6.65	7.25 – 7.50	
Transport width (m) Super-S2 boom	2.40		
Transport width (m) Super-L2 boom	3-section 2.40 4-section 2.65		
Empty weight (kg)	2,908 – 3,344	2,998 – 3,434	3,096 – 3,652
Pump capacity (l/min)	260/380		380
Max. suction capacity (l/min)	400/500		500
Ground clearance	up to 0.82 m		
Spraying height	0.5 – 2.5 m		
Operating pressure, max. (bar)	10		

Illustrations, content and technical data are not binding! Deviations of technical data are possible depending on the equipment. The illustrations may deviate from the requirements for local road traffic regulations.

✓ The small alternative: UG trailed sprayer

For smaller farms, AMAZONE offers the UG trailed sprayer with tank capacities of 2,200 or 3,000 litres.

More information can be found in the separate brochure for the UG.



✓ The big alternative: UX Super trailed sprayer

For larger farms, AMAZONE offers the UX Super trailed sprayer with tank capacities from 4,200 to 11,200 litres.

More information can be found in the separate brochure for the UX Super.

