



Technical data:

	ZA-XW 503	ZA-X 603	ZA-X 903	ZA-X 1403
Working width (m)	10–18 / 2 to 6 with row spreading attachment			
Hopper capacity (l)	500	600	900	1,400
– with bolt-on extension S 200 (l)	700	–	–	–
– with bolt-on extension S 250 (l)	–	850	–	–
– with bolt-on extension S 350 (l)	–	–	1,250	1,750
– with bolt-on extension L 800 (l)	–	–	1,700	–
Payload (kg)	1,000	1,000	1,800	1,800
Filling height (m)	0.93	0.91	0.97	1.16
– with bolt-on extension S 200 (l)	1.07	–	–	–
– with bolt-on extension S 250 (l)	–	1.05	–	–
– with bolt-on extension S 350 (l)	–	–	1.11	1.30
– with bolt-on extension L 800 (l)	–	–	1.25	–
Filling width (m)	0.90	1.40	1.89	1.89
– with bolt-on extension S 200 (l)	0.87	–	–	–
– with bolt-on extension S 250 (l)	–	1.37	–	–
– with bolt-on extension S 350 (l)	–	–	1.88	1.88
– with bolt-on extension L 800 (l)	–	–	2.48	–
Overall width (m)	1.07	1.50	2.02	2.02
– with bolt-on extension S 200 (l)	1.07	–	–	–
– with bolt-on extension S 250 (l)	–	1.55	–	–
– with bolt-on extension S 350 (l)	–	–	2.07	2.07
– with bolt-on extension L 800 (l)	–	–	2.65	–
Overall length (m)	1.42	1.42	1.30	1.30
Spreading disc speed (rpm)	540			
Weight of the base machine (kg)	194	212	248	275

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



AMAZONEN-WERKE H. DREYER SE & Co. KG

P. O. Box 51 · 49202 Hasbergen-Gaste/Germany

Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193