

FSP300, FSP500, FSP700 & FSP1000 Broadcast Spreaders

Specifications & Capacities				
Model Numbers	FSP300	FSP500	FSP700	FSP1000
Capacity (maximum Cu.ft. & pounds)	4.8 cu. ft. (288 lbs) [.14 m ³ (130.6 kg)]	5.83 cu. ft. (350 lbs) [.17 m ³ (158.8 kg)]	9.18 cu. ft. (563 lbs) [.26 m ³ (255.4 kg)]	12.18 cu. ft. (673 lbs) [.34 m ³ (305.3 kg)]
Overall dimensions	35 1/2" x 37.5" (.9 m x .95 m)	37" x 40" (0.94m x 1.02m)	44" x 46" (1.12m x 1.17m)	47" x 46" (1.19m x 1.17m)
Loading height	less than 36" (.91 m)	36" (0.91 m)	41" (1.04 m)	44.5" (1.13 m)
Weight	110 lbs (50 kg)	119 lbs (54 kg)	128 lbs (58 kg)	139 lbs (63 kg)
3-Point attachment	Category 1 (Quick Hitch Compatible)	Category 1	Category 1	Category 1
Net spreadable width				
Granular	up to 54 ft (16 m)	23-54 ft (7-16 m)	23-54 ft (7-16 m)	23-54 ft (7-16 m)
Crystalline	27 ft (8 m)	12-27 ft (4-8 m)	12-27 ft (4-8 m)	12-27 ft (4-8 m)
Power take-off shaft type	1 3/8"	1 3/8"	1 3/8"	1 3/8"
Transmission ratio	1:1	1:1	1:1	1:1
Min. tractor horsepower	15 hp (11.2 kW)	15 hp (11.2 kW)	18 hp (13.4 kW)	20 hp (14.9 kW)
Range of spreading Possibility				
lbs/acre	44 - 890	44 - 890	44 - 890	44 - 890
kgs/hectare	(49 - 998)	(49 - 998)	(49 - 998)	(49 - 998)

13613

