

RTR25 SERIES ROTARY TILLERS

25-75 HP | Cat. 1



Save time with reverse rotation.

A Reverse Tine Tiller turns up ground cover, chops it a time or two, and buries it under a cascade of large clods, which are buried under small clods. Large clods fall first, and they just get smaller as they pile on top of each other. What's left on top is a perfect seedbed to foster your wild imagination!

- Spring-loaded rear deflector levels the freshly tilled seedbed
- Hinged front flap with rubber insert helps prevent damage to deck from debris coming over the top of the tines
- Skid shoe on drive side has additional chain case protection



Sifting tines help "sift" the tilled material. Large or clumpy material falls first, with the top layer being a perfect consistency for planting. (Rear deflector removed for photo.)



The reverse rotation of the tiller tines forces the tiller in the ground, preventing "walking" on hard ground. Once it's in, it stays put!

3 YEAR
LIMITED GEARBOX
WARRANTY*

	RTR2570
Horsepower	25-75 HP
Hitch	Cat. 1
Width-Endplate to Endplate (cm)	70" (178)
Overall Width	76" (193)
Weight - lb (kg)	868 (394)
Number of Flanges	9
No. of Blades Per Flange	6 C-Shape
Blade Spacing	7-7/8"
Max. Tilling Depth ^	7"
Skid Shoe Settings	7
Offset	Up to 5"
Number of Sifting Tines	46
Rotor Swing Diameter	17"
Rotor Shaft Speed	220 rpm at 540 rpm PTO
PTO Driveline	Category 3 Slip Clutch
Gearbox	55 HP, 540 rpm, Cast Iron Housing, Drain Plug
Drive Chain	#100 High Tensile in Oil Bath
Sprockets	Hardened Teeth, Splined Center
Colors	

QUICK HITCH
SYSTEM

Land Pride
landpride.com

*See dealer for complete warranty information.

^ Tilling depth depends on conditions and fluffiness of tilled area.