

SRT62 & SRT76

Specifications & Capacities			SRT62	SRT76
Weight	lbs (kg)		785 (356)	880 (399)
Tilling width	in (m)		62 (1.57)	76 (1.93)
Overall width	in (m)		74 1/2 (1.89)	88 1/2 (2.25)
Tilling depth	in (cm)		2, 4, & 5.6 (5.1, 10.2, & 14.2)	2, 4, & 5.6 (5.1, 10.2, & 14.2)
Depth indicator (Patent-pending)			Depth indicator (Viewable from operator seat)	
Hydraulic requirements	gpm(Lpm)		14-23 (53-87)	
Hydraulic pressure range	psi (mPa)		2800 (19.3) min. / 4500 (31) max.	
Motor rpm (Depending on skid steer flow and pressure)			143 to 245 rpm	
Motor case drain			Standard	Standard
Number of rotor flanges			9	11
Number of tines per flange			4	4
Tine construction			Bi-directional forged hardened "C" shaped	
Direction of travel			Bi-directional (forward and reverse)	
Hitch type			Universal Quick Attach Hitch	
Side shift capabilities	in (cm)		6 (15.2) To the right	
Skid shoes			Replaceable	
Rotor swing diameter	in (cm)		18.3 (46.5)	
Number of shanks			5	6
Shank retainers			Spring loaded retaining clips 2	
Shank construction	in (mm)		3/4 x 2 1/2 x 16 (19 x 64 x 406) Adjustable hardened steel with 3 adjustable depths	
Construction	Deck plate End plates	in (mm)	1/4 (6) steel plate 3/8 (10) steel plate	

