

RTR05 Series

Specification & Capacities			
Model Number		RTR0542	RTR0550
Recommended tractor power take-off horsepower		Up to 26 hp (19.4 kW)(Subcompact Tractors)	
Weight	lbs (kg)	268 (121.6)	298 (135.2)
Tilling width	in (m)	42 (1.07)	50 (1.27)
Overall width		46 1/2 (1.18)	54 1/2 (1.38)
Hitch type		Category I Fits Land Pride's Category I Quick Hitch	
Offset capabilities		No	
Number of flanges		6	7
Number of tines per flange		4	
Tine construction		Alloy steel heat treated "C" shaped blades	
Skid shoes		Adjustable	
Storage stands		Adjustable	
Rear deflector		Adjustable	
Driveline		Category II Off-Center Shear-bolt - standard Slip-Clutch - optional	
Gearbox	hp (kW)	26 hp (19.4 kW) input at 540rpm 1.46:1 ratio Cast iron housing, straight bevel gears	
Gearbox lubrication and oil capacity		1 Pint of SAE 80-90W EP oil	
Drive chain		#80 Roller chain - Fully enclosed in oil bath with drain and fill plugs	
Chaincase Lubrication type Lubrication capacity	oz (L)	Shell Gadus S2 V2200 00 flowable grease or equivalent 20 oz (0,56 L)	
Sprockets		Case hardened teeth, splined bores	
Rotor swing diameter	in (cm)	13 (33)	
Rotor shaft speed		230 rpm at 540 rpm power take-off speed	

26794

