

Specifications

| | MT945C | MT955C | MT965C | MT975C |
|--------------------------------|-----------------|-----------------|-----------------|-----------------|
| Engine | CAT® C15 ACERT™ | CAT® C15 ACERT™ | CAT® C18 ACERT™ | CAT® C18 ACERT™ |
| Rated engine power @ 2,200 rpm | 430 Hp | 460 Hp | 510 Hp | 570 Hp |
| Rated engine power @ 2,200 rpm | 321 kW | 343 kW | 380 kW | 425 kW |
| Max power @ 2,000 rpm | 473 Hp | 506 Hp | 583 Hp | 609 Hp |
| Max power @ 2,000 rpm | 353 kW | 377 kW | 435 kW | 454 kW |
| Max torque @ 1,400 rpm | 2,134 Nm | 2,286 Nm | 2,525 Nm | 2,828 Nm |
| Engine displacement | 15.2 Litres | 15.2 Litres | 18.1 Litres | 18.1 Litres |

Transmission

| | | | | |
|----------------------------|-----------------|-----------------|-----------------|-----------------|
| Type | CAT® Powershift | CAT® Powershift | CAT® Powershift | CAT® Powershift |
| Forward and reverse speeds | 16 fwd x 4 rev |
| Max transport speed | 40 Kph | 40 Kph | 40 Kph | 40 Kph |

Rear Linkage

| | | | | |
|------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-----|
| Type | Optional Electronic Linkage Control | Optional Electronic Linkage Control | Optional Electronic Linkage Control | N/A |
| Draft sensing | Yes | Yes | Yes | N/A |
| Lift capacity - at link ends | 14,000 Kg | 14,000 Kg | 14,000 Kg | N/A |
| Size category | Cat IV | Cat IV | Cat IV | N/A |

Specifications common to all models

Hydraulic System

| | |
|-----------------------------|--|
| Type | LIFD with Priority function |
| Number of rear spool valves | Up to six |
| Max flow | Standard 166 Litre/min Optional 223 Litre/min |
| Max pressure | 200 Bar |

Optional Equipment

Climate Control
Deluxe VRS seat
Nightbreaker work lights

Operator Environment

Noise level 73 dB(A)

Fuel Tank Capacity

1,500 Litres