


SPECIFICATIONS

MODEL		M5040	M6040	M7040	
Engine	Model	KUBOTA-V3007-DI		KUBOTA-V3307-DI	
	Type (Make: KUBOTA)	4-cylinder in-line direct injected		4-cylinder in-line direct injected	
	SAE Net Power	HP (kW)	50.5 (37.7)	62.0 (46.3)	67.0 (50.0)
	PTO horsepower	HP (kW)	45.0 (33.6)	55.0 (41.0)	62.0 (46.3)
	Total Displacement	cu.in. (cc)	186 (3053)	203 (3331)	203 (3331)
	Bore X Stroke	in. (mm)	3.70 X 4.30 (94X110)	3.70 X 4.70 (94X120)	3.70 X 4.70 (94X120)
	Rated speed	rpm	2600	2600	2600
	Fuel tank capacity	gal. (l)	18.5 (70) ROPS Models / 29.1 (110) CAB Models		
	Alternator/Battery		45 Amps / 12V 900 CCA ROPS Models 60 Amps / 12V 900 CCA ROPS Models		
	Air cleaner		8 in. dry, dual element		
Muffler / Exhaust Pipe		Left side of hood vertical / Underhood muffler ROPS Models			
Transmission	No. of speeds (Option)	Cassette Type creep speed 12F X 12R			
	Main gear shift	4-speed main transmission, synchronized shift			
	Range gear shift	2-speed High / Low Constant Mesh			
	Shuttle shift	Synchro-Shuttle standard 2wd & 4wd models Hydraulic-Shuttle Optional on CAB Models			
	Creep Speed (Cassette type, optional)	mph	0.20, 0.29, 0.39, 0.63	0.21, 0.30, 0.40, 0.65	0.22, 0.31, 0.42, 0.68
	Max. travel speed	mph	17.4	18	18.7
	Main clutch type/diameter	in. (mm)	Synchro Shuttle , cerametallic button dry clutch 10.8 (275) Hydraulic Shuttle = Multi-Plate wet disc clutch 6 disks, 4.9 (125)		
	Brake type		Mechanically operated wet disc brakes		
PTO System	PTO type	Live-Independent PTO, Hydraulically operated wet clutch, w/PTO brake			
	PTO Speed	540 rpm (6 splines) standard			
Hydraulics	Pump flow (Hitch & remotes)	gpm (l/min)	11.0 (41.6)		
	Pump flow (Power steering)	gpm (l/min)	6.1 (23.0)		
	3-point hitch (Category II)		Telescopic lower link ends, Telescopic stabilizers		
	Control system		Mechanical position and mixed draft control, Top link draft sensing		
	Lift capacity 24" behind lift point	lbs. (kg)	Standard 3307 (1500)		
Remote valves		1 standard (2nd or 3rd. Optional)			
Steering		Hydrostatic power steering			
Cab	Operator area	ISO-mounted flat deck, Hanging Pedals, Tilt steering wheel			
	Seat	Reclining, fully adjustable; height, weight, fore & aft., arm rests, with retractable seat belt			



SPECIFICATIONS

MODEL		M5040	M6040	M7040
Cab (cont.)	Lighting	ROPS: 2 headlights, 2 corner lights, 2 tail lights, 2 frt. and 4 rear safety flashers CAB: 2 headlights, 2 corner lights, 2 tail lights, 2 frt. and 4 rear safety flashers 2 front worklights, 2 rear work lights.		
	Standard Cab Features	Ultra Grand Cab has an arched Beam roof line, Heater/Air conditioner, Sun visor, Front wiper/washer, Beverage holder, 12V/30 amp 3-Pin Electric outlet, Tinted glass, 2 external mirrors, 3-Position switch for Interior light 7-pin Trailer electric outlet, Optional Air Ride seat suspension.		
Dimensions & Weight	Wheelbase	2wd Models: ROPS 82.1 (2085) Cab 84.4 (2145) 4wd Models: ROPS 80.7 (2250) Cab 83.1 (2110)		
	Overall width (minimum)	73.2 (1860)		
	Overall length	2wd 140.4 (3565) / 4wd 135.6 (3445)		
	Overall height ROPS/CAB	95.3 (2420) / 98.2 (2495)	96.9 (2460) / 99.8 (2535)	97.2 (2470) / 100.2 (2545)
	Crop clearance	16.5 (420)		16.9 (430)
	Tread width Front 2WD	56.7-72.4 (1440-1840)		
	Tread width Front 4WD	52.4-56.3 (1330-1430)		55.9-59.9 (1420-1520)
	Tread width Rear	52.0-67.7 (1420-1720)	55.9 - 67.7 (1420-1720)	
	Turning radius (w/o brake)	2wd 11.2 (3.3)		4wd 11.8 (3.6)
	Weight (w/Standard tire/Steel dish)	2wd 3748 (1700) 4wd 3968 (1800)	3858 (1750) / 4079 (1850)	4475 (2030) / 4608 (2090)
	Standard front tire	6.50-16 2wd / 9.5-24 4wd	7.50-16 2wd / 12.4-24 4wd	7.50-16 2wd / 9.5-24 4wd
	Standard rear tire	14.9-28	16.9-28	16.9-30
Other optional equipment		Front weight bumper (std 2wd) Front weights, Rear wheel weights, Drawbar clevis (hammerstrap), 2nd and 3rd remote valves, Cassette type Creep speed, Rear axle spacer kit, Cab Radio cassette or CD Player with 7-Channel weather band, Grill Guard, Down Exhaust, Deluxe canopy for ROPS Models.		

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

Not for sale in Nebraska