

B2301 - B2601 Implements



COMPETITIVE COMPARISON						
MODEL		Kubota B2301/B2601 LA434 Loader	John Deere 2025R H130 Loader	Mahindra Max 24 HST Max 24L	Mahindra Max 26 HST Max 26L	
LOADER	Lift Capacity (Pivot Pin, Max. Height)	lb.	948	1023	900	1402
	Lift Capacity (500mm Forward Pivot Pin, Max. Height)	lb.	659	N/P	N/P	N/P
	Lift Height (Pivot Pin)	in.	78.5	78.7	75.0	82.7
	Reach at Maximum Height	in.	15.4	-	23.0	29.0
	Boom Breakout Force (Pivot Pin)	lb.	2146	2508	2000	2690
	Boom Breakout Force (500mm Forward Pivot Pin)	lb.	1520	N/P	N/P	N/P
	Digging Depth at Bucket Level	in.	3.8	3.7	4.0	2.6
	Cycle Times - Loader Raise	sec.	3.7	4.7	3.7	3.3
	Cycle Times - Loader Lower	sec.	2.7	2.9	2.6	2.4
	Cycle Times - Bucket Dump	sec.	1.9	4.7	3.4	2.2
	Cycle Times - Bucket Rollback	sec.	2.6	2.9	2.9	2.6
	Bucket Angle - Dump Angle	degrees	40.0	38	38	32
	Bucket Angle - Rollback Angle	degrees	25.0	24.5	20	24
	Quick Attach Loader		Optional	Standard	N/P	N/P
MODEL		Kubota B2301/B2601 BH70 Backhoe	John Deere 2025R 270A Backhoe	Mahindra Max 24 HST Max 24B	Mahindra Max 26 HST Max 26B	
BACKHOE	Digging Depth at 2' flat bottom	in.	85.2 (2165)	84	80	80.0
	Swing Arc	degrees	140.0	150.0	140.0	150.0
	Bucket Cylinder Digging Force	lb.	2900 (1315)	2474	2050	2270
	Dipperstick Cylinder Digging Force	lb.	1600 (726)	1502	1256	1248
	Loading Height	in.	61.6 (1474)	67	60	62
	Reach from Swing Point	in.	116.8 (2966)	117.0	98.0	102.0
	6-Positional Mechanical Thumb		Optional	Optional	N/P	N/P

N/A = Not Available N/P = Not Published

* Non Self Leveling Loader

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.