

KUBOTA GrandL30 Series Specifications

MODEL : L3130

		F (2WD)	DT (4WD)	GST (4WD)	HST (4WD)
Engine					
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel			
Engine gross power	HP (kW)	32.1 (23.9)			
Engine net power	HP (kW)	31.0 (23.2)			
PTO power	HP (kW)	25.5 (19.1)			24.0 (17.9)
No. of cylinders		3			
Bore &stroke	in. (mm)	3.3 × 3.6 (83 × 92.4)			
Total displacement	cu.in. (cc)	91.5 (1499)			
Rated speed	rpm	2700			
Battery		75D 26R, 12V			
Alternater		12V, 40A			
Fuel tank capacity	US gal. (ℓ)	10.6 (40)			
PTO					
Rear PTO					
Revolution		1 speed: 540 rpm			
Type		Independent			Independent* ²⁾
Mid PTO		Option			
Revolution		1 speed: 2000 rpm			
Hydraulic					
Lift control type: Position		Standard			
Draft		Option			
Implement pump	GPM (ℓ /min.)	8.3 (31.5)			
Power steering pump	GPM (ℓ /min.)	4.9 (18.6)			
Total hydraulic flow	GPM (ℓ /min.)	13.2 (50.1)			
3-point hitch		Category I			
Lift capacity at 24 in. behind lift point	lbs. (kg)	2650 (1200)			
Travelling System					
Transmission		FST 8F/8R		GST 12F/8R	HST (3 Ranges)
Steering		Hydrostatic power steering			
Brake		Wet disc type			
Clutch		Dry type single stage			
Standard tire size*¹⁾		Front	6.0-16	7.2-16	7.2-16
	Rear	12.4-24			
Travel speeds					
No.of speeds (at rated engine speed)		GST* ³⁾		Optional creep speeds for GST* ³⁾	
		12 Foward /8 Reverse		12 Foward /8 Reverse	
	mph (km/h)	Forward	Reverse	Forward	Reverse
First		1.0 (1.6)	1.0 (1.6)	0.11 (0.18)	0.11 (0.17)
Second		1.4 (2.3)	1.3 (2.2)	0.16 (0.25)	0.15 (0.24)
Third		1.9 (3.1)	2.2 (3.6)	0.21 (0.34)	0.24 (0.39)
Fourth		2.3 (3.7)	3.2 (5.2)	0.26 (0.41)	0.36 (0.58)
Fifth		2.8 (4.5)	4.6 (7.5)	0.31 (0.51)	0.52 (0.84)
Sixth		3.4 (5.5)	6.6 (10.7)	0.38 (0.61)	0.74 (1.19)
Seventh		4.0 (6.5)	10.7 (17.2)	0.45 (0.73)	1.20 (1.93)
Eighth		4.9 (7.8)	15.7 (25.4)	0.55 (0.88)	1.77 (2.85)
Ninth		5.7 (9.2)		0.64 (1.03)	
Tenth		6.9 (11.1)		0.77 (1.24)	
Eleventh		11.2 (18.0)		1.25 (2.02)	
Twelfth		16.5 (26.6)		1.85 (2.98)	
Dimensions					
Overall length (w/o 3P)	in. (mm)	119.1 (3025)	114.8 (2915)		
Overall width (min. tread)	in. (mm)	59.8 (1520)			
Overall height (w/ROPS)	in. (mm)	90.7 (2305)			
Wheelbase	in. (mm)	71.3 (1810)	71.1 (1805)		
Min. ground clearance	in. (mm)	14.2 (360)			
Tread	Front	(Front tire)	47.6 (1210)	45.5 (1155)	
		in. (mm)	51.6 (1310)		
			55.5 (1410)		
			59.4 (1510)		
	Rear	(Rear tire)	47.2 (1200)		
		in. (mm)	51.2 (1300)		
			54.5 (1385)		
			58.3 (1480)		
Min.turning radius (w/brake, 4WD disengaged)		feet (m)	8.5 (2.6)	8.9 (2.7)	
Weight (with ROPS)		lbs. (kg)	3120 (1415)	3220 (1460)	3260 (1480)
					3305 (1500)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

^{*1)} Kubota offers several tire options.

^{*2)} With Master Clutch.

^{*3)} Speeds 3, 5, 7 and 9 of the GST are not included in the FST's 8 forward speeds.