



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON				
FEATURE		KUBOTA L3240	JOHN DEERE 3320	NEW HOLLAND TC29DA
Engine				
Engine Manufacturer		Kubota	Yanmar	Shibaura
Gross Horsepower	HP	34	32.5	29
PTO Horsepower	HP	26.5 Gear or 25.0 Hydro	25.5 Gear or 25.0 Hydro	25 Gear or 23.6 Hydro
Rated Speed	RPM	2700	2600	2800
No. Cylinders/Displacement	cu. in.	3 / 100.5	3 / 100	3 / 81.2
Fuel Tank Capacity	gal.	11.6	13.5	7.3
Air Cleaner		Dual Element	Dual Element	Dual Element
Dimensions				
Wheelbase	in.	71.3 (2WD) , 71.1 (4WD)	68	63
Overall Length (w/out 3-pt hitch)	in.	119.3 (2WD) , 114.8 (4WD)	Info N/A	106.2 (w/ 3-pt hitch)
Overall Width (min. tread)	in.	59.8	Info N/A	54.3
Overall Height (top of ROPS)	in.	90.7	Info N/A	87.8
Weight (inc. std. tires and ROPS)	lbs.	3153(F),3252(DT),3296(GST) 3395 (HST) , 3748 (HSTC)	2900	2440 Gear or 2474 Hydro
Min. Ground Clearance	in.	14.0	Info N/A	Info N/A
Transmission / Drive Train				
Transmission		Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic	Collar Shift or Hydrostatic
Manual Speeds		8F/8R Gear, 12F/8R, or 3 Range Hydro (Plus Hi/Lo)	12F/12R Gear or 3 Range Hydro	9F/3R or 3 Range Hydro
Hydrostatic Transmission Functions		Load Sensing, Hi/Lo, Response Control, Auto-Throttle	Load Sensing, Response Control	N/A
Creep Speed		Optional (Gear-Drive Only)	N/A	N/A
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc
Clutch Diameter	in.	9.4	4.4	8.5
Clutch		Dry Type - Single Stage	Wet Disc	Info N/A



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L3240	JOHN DEERE 3320	NEW HOLLAND TC29DA
PTO System				
Type		Independent	Independent	Live
Rear PTO	RPM	540	540	540
Mid PTO	RPM	Optional 2000	Optional 2100	Opt (Gear) / Std (Hydro) 2000
Hydraulic System / 3-Point Hitch				
Hitch Category (SAE)		Category I	Category I	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only	Telescopic Stabilizers and Flexible Link Ends
Pump Capacity (Main/PS)	gpm	8.3 / 4.9	8.6 / 5.3	7.6 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2650	2200	1635
Draft Control/Top-n-Tilt Kit		Optional / Optional	N/A / Optional	N/A
Steering		Hydrostatic	Hydrostatic	Hydrostatic
Standard Tires				
Front Tire		6.0-16 (2WD) , 7.2-16 (4WD)	7-14	7-14
Rear Tire		12.4-24	11.2-24	11.2-24



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L3240	JOHN DEERE 3320	NEW HOLLAND TC29DA
Other Specifications				
Deck		Flat	Flat	Semi-Flat
Width Between Fenders	in.	31.5	24.4	25.5
Min. Turning Radius	ft.	8.5 (2WD) , 8.9 (4WD)	8.8	Info N/A
Cruise Control		Standard (Hydro Only)	Standard	Standard (Hydro Only)
Alternator	amps	40 (55 on Cab Models)	40	40
Rear Differential Lock		Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Optional
Drawbar		Adj. Drawbar Std/Swinging Optional	Adjustable Drawbar	Swinging
Foldable ROPS		Standard	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard
Tool Box		Standard	Standard	Standard
Cup Holder		Standard	Standard	N/A
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional
Reclining Seat		Standard	N/A	N/A
Kubota Intellipanel		Standard	N/A	N/A
Rubber Mat		Standard	Standard	Standard
Underhood Muffler		Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L3540	NEW HOLLAND TC33DA
Engine			
Engine Manufacturer		Kubota	Shibaura
Gross Horsepower	HP	37	33
PTO Horsepower	HP	29.5 Gear or 28.0 Hydro	28.6 Gear or 26.9 Hydro
Rated Speed	RPM	2700	2800
No. Cylinders/Displacement	cu. in.	3 / 111.4	3 / 91.3
Fuel Tank Capacity	gal.	11.6	7.3
Air Cleaner		Dual Element	Dual Element
Dimensions			
Wheelbase	in.	71.1	63
Overall Length (w/out 3-pt hitch)	in.	115	106.2 (w/ 3-pt hitch)
Overall Width (min. tread)	in.	59.8	54.3
Overall Height (top of ROPS)	in.	90.7	87.8
Weight (inc. std. tires and ROPS)	lbs.	3296(GST),3395(HST),3748(HSTC)	2440 Gear or 2474 Hydro
Min. Ground Clearance	in.	14.0	Info N/A
Transmission / Drive Train			
Transmission		Synchronized Shuttle or Hydrostatic	Collar Shift or Hydrostatic
Manual Speeds		12F/8R, or 3 Range Hydro (Plus Hi/Lo)	9F/3R or 3 Range Hydro
Hydrostactic Transmission Functions		Load Sensing, Hi/Lo, Response Control, Auto-Throttle	N/A
Creep Speed		Optional (Gear-Drive Only)	N/A
Brakes		Multiple Wet Disc	Wet Disc
Clutch Diameter	in.	9.4	8.9
Clutch		Dry Type - Single Stage	Info N/A



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L3540	NEW HOLLAND TC33DA
PTO System			
Type		Independent	Live
Rear PTO	RPM	540	540
Mid PTO	RPM	Optional 2000	Opt (Gear) / Std (Hydro) 2000
Hydraulic System / 3-Point Hitch			
Hitch Category (SAE)		Category I	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers and Flexible Link Ends
Pump Capacity (Main/PS)	gpm	8.3 / 4.9	7.6 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2650	1635
Draft Control/Top-n-Tilt Kit		Optional / Optional	N/A
Steering		Hydrostatic	Hydrostatic
Standard Tires			
Front Tire		7.2-16	7-14
Rear Tire		12.4-24	11.2-24



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L3540	NEW HOLLAND TC33DA
Other Specifications			
Deck		Flat	Semi-Flat
Width Between Fenders	in.	31.5	25.5
Min. Turning Radius	ft.	8.9	Info N/A
Cruise Control		Standard (Hydro Only)	Standard (Hydro Only)
Alternator	amps	40 (55 on Cab Models)	40
Rear Differential Lock		Standard	Standard
Entry/Exit Step		Standard	Optional
Drawbar		Adj. Drawbar Std/Swinging Optional	Swinging
Foldable ROPS		Standard	Standard
Tilt Steering Wheel		Standard	Standard
Tool Box		Standard	Standard
Cup Holder		Standard	N/A
Deluxe Seat with Armrests		Standard	Armrests Optional
Reclining Seat		Standard	N/A
Kubota Intellipanel		Standard	N/A
Rubber Mat		Standard	Standard
Underhood Muffler		Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON					
FEATURE		KUBOTA L3940	JOHN DEERE 3520	NEW HOLLAND TC35A/DA	
Engine					
Engine Manufacturer		Kubota	Yanmar	Shibaura	
Gross Horsepower	HP	40.5	37	35	
PTO Horsepower	HP	33.0 Gear or 31.5 Hydro	30.5 Gear or 30.0 Hydro	29.6 Gear or 29.1 Hydro	
Rated Speed	RPM	2700	2600	2600	
No. Cylinders/Displacement	cu. in.	4 / 122.0	3 / 91.5	3 / 101.1	
Fuel Tank Capacity	gal.	13.2	13.5	13	
Air Cleaner		Dual Element	Dual Element	Dual Element	
Dimensions					
Wheelbase	in.	74.6	68	73.5	
Overall Length (w/out 3-pt hitch)	in.	121.5	Info N/A	125.2 (w/ 3-pt hitch)	
Overall Width (min. tread)	in.	66.5	Info N/A	66.6	
Overall Height (top of ROPS)	in.	97.4	Info N/A	95.5	
Weight (inc. std. tires and ROPS)	lbs.	3483(DT), 3527(GST), 3627(HST), 3968(HSTC)	2900	3009 (2WD), 3096 (4WD) or 3252 (Hydro)	
Min. Ground Clearance	in.	14.6	Info N/A	Info N/A	
Transmission / Drive Train					
Transmission		Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic	
Manual Speeds		8F/8R Gear, 12F/8R, or 3 Range Hydro	12F/12R Gear or 3 Range Hydro	12F/12R or 2 Range Hydro	
Hydrostatic Transmission Functions		Load Sensing, Hi/Lo, Response Control, Auto-Throttle	Load Sensing, Response Control	Hi/Lo	
Creep Speed		Optional (Gear-Drive Only)	N/A	N/A	
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc	
Clutch Diameter	in.	10.2(Gear)/9.4(HST)	Info N/A	Info N/A	
Clutch		Dry Type - Single Stage	Wet Disc	Info N/A	



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON					
FEATURE		KUBOTA L3940	JOHN DEERE 3520	NEW HOLLAND TC35A/DA	
PTO System					
Type		Independent	Independent	Independent	
Rear PTO	RPM	540	540	540	
Mid PTO	RPM	Optional 2000	Optional 2100	N/A (Gear) / Opt (Hydro) 2000	
Hydraulic System / 3-Point Hitch					
Hitch Category (SAE)		Category I	Category I	Category I	
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only	Telescopic Stabilizers and Flexible Lower Links (Standard (DA) / Optional (A))	
Pump Capacity (Main/PS)	gpm	9.8 / 4.9	8.6 / 5.3	9.8 / 5.1	
Lift Capacity at 24" Behind L.P.	lbs.	2760	2200	2025	
Draft Control/Top-n-Tilt Kit		Optional / Optional	N/A / Optional	Optional / N/A	
Steering		Hydrostatic	Power	Hydrostatic	
Standard Tires					
Front Tire		8.3-16	7-14	5.5-16 / 7-16	
Rear Tire		14.9-24	11.2-24	13.6-24	



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L3940	JOHN DEERE 3520	NEW HOLLAND TC35A/DA
Other Specifications				
Deck		Flat	Flat	Semi-Flat
Width Between Fenders	in.	31.5	24.4	30
Min. Turning Radius	ft.	8.9	8.8	Info N/A
Cruise Control		Standard (Hydro Only)	Standard	Standard (Hydro Only)
Alternator	amps	40 (55 on Cab Models)	40	40
Rear Differential Lock		Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Standard
Drawbar		Adj. Drawbar Std/ Swinging Optional	Adjustable Drawbar	Swinging
Foldable ROPS		Standard	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard (DA) / N/A (A)
Tool Box		Standard	Standard	Standard (DA)/Optional (A)
Cup Holder		Standard	Standard	Standard(DA)/Optional (A)
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional (DA)/N/A (A)
Reclining Seat		Standard	N/A	N/A
Kubota Intellipanel		Standard	N/A	N/A
Rubber Mat		Standard	Standard	Standard
Underhood Muffler		Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L4240	JOHN DEERE 3720	JOHN DEERE 4120	NEW HOLLAND TC40A/DA
---------	--	-----------------	--------------------	--------------------	-------------------------

Engine

Engine Manufacturer		Kubota	Yanmar	JD (Mexico)	Shibaura
Gross Horsepower	HP	44	44.0	43.0	40
PTO Horsepower	HP	36.5 Gear or 35.0 Hydro	35.0	35.5 GR/ 35.0 HYD	35 Gear or 33.2 Hydro
Rated Speed	RPM	2700	2600	2400	2600
No. Cylinders/Displacement	cu. in.	4 / 134.1	3 / 101.1	4 / 149	4 / 121.7
Fuel Tank Capacity	gal.	13.2	13.5	14.5	13
Air Cleaner		Dual Element	Dual Element	Dual Element	Dual Element

Dimensions

Wheelbase	in.	74.6	68	71.5	73.5
Overall Length (w/out 3-pt hitch)	in.	121.5	Info N/A	Info N/A	125.2 (w/ 3-pt hitch)
Overall Width (min. tread)	in.	66.5	Info N/A	Info N/A	66.6
Overall Height (top of ROPS)	in.	97.4	Info N/A	Info N/A	95.5
Weight (inc. std. tires and ROPS)	lbs.	3527(DT), 3571(GST), 3671(HST), 4001(HSTC)	2900	3700	3300 Gear or 3328 Hydro
Min. Ground Clearance	in.	14.6	Info N/A	Info N/A	Info N/A

Transmission / Drive Train

Transmission		Synchronized Shuttle or Hydrostatic	Hydrostatic Only	Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic
Manual Speeds		8F/8R Gear, 12F/8R, or 3 Range Hydro	3 Range	12F/12R Gear or 3 Range Hydro	12F/12R or 2 Range Hydro
Hydrostactic Transmission Functions		Load Sensing, Hi/Lo, Response Control, Auto-Throttle	Load Sensing, Response Control	Load Sensing, Response Control	Hi/Lo
Creep Speed		Optional (Gear-Drive)	N/A	N/A	N/A
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc	Wet Disc
Clutch Diameter	in.	10.2(Gear)/9.4(HST)	Info N/A	5.1	Info N/A
Clutch		Dry Type - Single Stage	Info N/A	Wet Disc	Info N/A



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L4240	JOHN DEERE 3720	JOHN DEERE 4120	NEW HOLLAND TC40A/DA
PTO System					
Type		Independent	Independent	Independent	Independent
Rear PTO	RPM	540	540	540	540
Mid PTO	RPM	Optional 2000	Optional 2100	Optional 2100	N/A (Gear) / Opt (Hydro) 2000
Hydraulic System / 3-Point Hitch					
Hitch Category (SAE)		Category I	Category I	Category I	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers	Telescopic Stabilizers	Telescopic Stabilizers and Flexible Lower Links (Standard (DA) / Optional (A))
Pump Capacity (Main/PS)	gpm	9.8 / 4.9	8.6 / 5.3	12 / 5.1	9.8 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2760	2200	2500	2330
Draft Control/Top-n-Tilt Kit		Optional / Optional	N/A / Optional	N/A / Optional	Optional / N/A
Steering		Hydrostatic	Power	Power	Hydrostatic Power Steering
Standard Tires					
Front Tire		8.3-16	7-14	8-16	7-16
Rear Tire		14.9-24	11.2-24	13.6-28	13.6-24



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L4240	JOHN DEERE 3720	JOHN DEERE 4120	NEW HOLLAND TC40A/DA
Other Specifications					
Deck		Flat	Flat	Flat	Semi-Flat
Width Between Fenders	in.	31.5	24.4	31.5	30
Min. Turning Radius	ft.	8.9	8.8	8.8	Info N/A
Cruise Control		Standard (Hydro Only)	Standard	Standard	Standard (Hydro Only)
Alternator	amps	40 (55 on Cab Models)	40	75	40
Rear Differential Lock		Standard	Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Standard	Standard
Drawbar		Adj. Drawbar Std/ Swinging Optional	Adjustable Drawbar	Adjustable Drawbar	Swinging
Foldable ROPS		Standard	Standard	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard	Standard (DA) / N/A (A)
Tool Box		Standard	Standard	Standard	Standard (DA) / Optional (A)
Cup Holder		Standard	Standard	Standard	Standard (DA) / Optional (A)
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional	Armrests Optional (DA)/N/A (A)
Reclining Seat		Standard	N/A	N/A	N/A
Kubota Intellipanel		Standard	N/A	N/A	N/A
Rubber Mat		Standard	Standard	Standard	Standard
Underhood Muffler		Standard	Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.



Compact Tractors



L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L4740	JOHN DEERE 4320	NEW HOLLAND TC45A/DA	NEW HOLLAND TC48DA
---------	--	-----------------	--------------------	-------------------------	-----------------------

Engine					
Engine Manufacturer		Kubota	JD (Mexico)	Shibaura	Shibaura
Gross Horsepower	HP	49	48.0	45	48
PTO Horsepower	HP	41.5 Gear or 40.0 Hydro	40.5 Gear or 40 Hydro	39.6 Gear or 37.8 Hydro	40
Rated Speed	RPM	2700	2400	2600	2800
No. Cylinders/Displacement	cu. in.	4 / 148.5	4 / 149	4 / 135.2	4 / 135.2
Fuel Tank Capacity	gal.	14.3	14.5	13	13.5
Air Cleaner		Dual Element	Dual Element	Dual Element	Dual Element

Dimensions					
Wheelbase	in.	74.6	71.5	73.5	74.8
Overall Length (w/out 3-pt hitch)	in.	121.5	Info N/A	125.2 (w/ 3-pt hitch)	137.3 (w/ 3pt hitch)
Overall Width (min. tread)	in.	66.5	Info N/A	66.6	64.4
Overall Height (top of ROPS)	in.	100.6	Info N/A	95.5	95
Weight (inc. std. tires and ROPS)	lbs.	3751(GST), 3671(HST), 4001(HSTC)	3700	3349 Gear or 3633 Hydro	3976
Min. Ground Clearance	in.	14.6	Info N/A	Info N/A	Info N/A

Transmission / Drive Train					
Transmission		Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic	Synchronized Shuttle or Hydrostatic	Synchronized Shuttle
Manual Speeds		8F/8R Gear, 12F/8R, or 3 Range Hydro	12F/12R Gear or 3 Range Hydro	12F/12R or 4 Range Hydro	12F / 12R
Hydrostactic Transmission Functions		Load Sensing, Hi/Lo, Response Control, Auto-Throttle	Load Sensing, Response Control	Hi/Lo	N/A
Creep Speed		Optional (Gear-Drive)	N/A	N/A	N/A
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc	Wet Disc
Clutch Diameter	in.	10.2(Gear)/9.4(HST)	5.1	Info N/A	Info N/A
Clutch		Dry Type - Single Stage	Wet Disc	Info N/A	Info N/A



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L4740	JOHN DEERE 4320	NEW HOLLAND TC45A/DA	NEW HOLLAND TC48DA
---------	--	-----------------	--------------------	-------------------------	-----------------------

PTO System					
Type		Independent	Independent	Independent	Independent
Rear PTO	RPM	540	540	540	540
Mid PTO	RPM	Optional 2000	Optional 2100	N/A (Gear) / Opt (Hydro) 2000	N/A

Hydraulic System / 3-Point Hitch					
Hitch Category (SAE)		Category I	Category I	Category I	Category I and II
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only	Telescopic Stabilizers and Flexible Lower Links (Std (DA) / Opt (A)	Telescopic Stabilizers and Flexible Lower Links
Pump Capacity (Main/PS)	gpm	9.8 / 4.9	12 / 5.1	9.8 / 5.1	12.03 / 5.52
Lift Capacity at 24" Behind L.P.	lbs.	2760	2500	2330	3465
Draft Control/Top-n-Tilt Kit		Optional / Optional	N/A / Optional	Optional / N/A	Standard / N/A
Steering		Hydrostatic	Power	Hydrostatic	Hydrostatic

Standard Tires					
Front Tire		8.3-16	8-16	7-16	8-16
Rear Tire		14.9-24	13.6-28	13.6-24	14.9-24



Compact Tractors



L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE	KUBOTA	JOHN DEERE	NEW HOLLAND	NEW HOLLAND
	L4740	4320	TC45A/DA	TC48DA

Other Specifications					
Deck		Flat	Flat	Semi-Flat	Semi-Flat
Width Between Fenders	in.	31.5	31.5	30	30
Min. Turning Radius	ft.	8.9	9.2	Info N/A	Info N/A
Cruise Control		Standard (Hydro Only)	Standard (Hydro Only)	Standard (Hydro Only)	N/A
Alternator	amps	40 (55 on Cab Models)	75	40	40
Rear Differential Lock		Standard	Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Standard	Standard
Drawbar		Adj. Drawbar Std/ Swinging Optional	Adjustable Drawbar	Swinging	Swinging
Foldable ROPS		Standard	Standard	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard (DA) / N/A (A)	Standard
Tool Box		Standard	Standard	Std (DA) / Opt (A)	Standard
Cup Holder		Standard	Standard	Std (DA) / Opt (A)	Standard
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional (DA) / N/A (A)	Armrests Optional
Reclining Seat		Standard	N/A	N/A	N/A
Kubota Intellipanel		Standard	N/A	N/A	N/A
Rubber Mat		Standard	Standard	Standard	Standard
Underhood Muffler		Standard	Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON				
FEATURE		KUBOTA L5040	JOHN DEERE 4520	NEW HOLLAND TC55DA
Engine				
Engine Manufacturer		Kubota	JD (Mexico)	Shibaura
Gross Horsepower	HP	52	Info N/A	Info N/A
PTO Horsepower	HP	44	45.5	47
Rated Speed	RPM	2600	2400	Info N/A
No. Cylinders/Displacement	cu. in.	4 / 148.5	4 / 149	4 / 135.2
Fuel Tank Capacity	gal.	14.3	14.5	13.5
Air Cleaner		Dual Element	Dual Element	Dual Element
Dimensions				
Wheelbase	in.	75.4	71.5	74.8
Overall Length (w/out 3-pt hitch)	in.	126.4	Info N/A	Info N/A
Overall Width (min. tread)	in.	67.3	Info N/A	Info N/A
Overall Height (top of ROPS)	in.	101	Info N/A	Info N/A
Weight (inc. std. tires and ROPS)	lbs.	3803	3700	3377
Min. Ground Clearance	in.	15.7	Info N/A	Info N/A
Transmission / Drive Train				
Transmission		Synchronized Shuttle	Synchronized Shuttle	Synchronized Shuttle
Manual Speeds		12F/8R	12F / 12R	12F / 12R
Creep Speed		Optional	N/A	N/A
Brakes		Multiple Wet Disc	Wet Disc	Wet Disc
Clutch Diameter	in.	10.2	5.1	Info N/A
Clutch		Dry Type - Single Stage	Wet Disc	Dry



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON				
FEATURE		KUBOTA L5040	JOHN DEERE 4520	NEW HOLLAND TC55DA
PTO System				
Type		Independent	Independent	Independent
Rear PTO	RPM	540	540	540
Mid PTO	RPM	Optional 2000	Optional 2100	N/A
Hydraulic System / 3-Point Hitch				
Hitch Category (SAE)		Category I and II	Category I	Category I and II
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower	Telescopic Stabilizers Only	Telescopic Stabilizers and Flexible Lower Links
Pump Capacity (Main/PS)	gpm	9.4 / 4.7	12 / 5.1	11.6 / Info N/A
Lift Capacity at 24" Behind L.P.	lbs.	2760	2500	3463
Draft Control/Top-n-Tilt Kit		Optional / Optional	Optional / Optional	Optional / Info N/A
Steering		Hydrostatic	Power	Hydrostatic
Standard Tires				
Front Tire		9.5-16	8-16	9.5-16
Rear Tire		14.9-26	13.6-28	14.9-28



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON				
FEATURE		KUBOTA L5040	JOHN DEERE 4520	NEW HOLLAND TC55DA
Other Specifications				
Deck		Flat	Flat	Semi-Flat
Width Between Fenders	in.	31.5	31.5	30
Min. Turning Radius	ft.	9.2	9.2	9.2
Alternator	amps	45	75	40
Rear Differential Lock		Standard	Standard	Standard
Entry/Exit Step		Standard	Standard	Standard
Drawbar		Adj. Drawbar Std / Swinging Optional	Adjustable Drawbar	Swinging
Foldable ROPS		Standard	Standard	Standard
Tilt Steering Wheel		Standard	Standard	Standard
Tool Box		Standard	Standard	Optional
Cup Holder		Standard	Standard	Standard
Deluxe Seat with Armrests		Standard	Armrests Optional	Armrests Optional
Reclining Seat		Standard	N/A	N/A
Kubota Intellipanel		Standard	N/A	N/A
Rubber Mat		Standard	Standard	Optional
Underhood Muffler		Standard	Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.



COMPARISON

FEATURE		KUBOTA L5240	JOHN DEERE 4520
Engine			
Engine Manufacturer/Model		Kubota	JD (Mexico)
Gross Horsepower	HP	54	Info N/A
PTO Horsepower	HP	45	45
Rated Speed	RPM	2600	2400
No. Cylinders/Displacement	cu. in.	4 / 148.5	4 / 149
Fuel Tank Capacity	gal.	14.3	14.5
Air Cleaner		Dual Element	Dual Element
Dimensions			
Wheelbase	in.	75.4	71.5
Overall Length (w/out 3-pt hitch)	in.	126.4	Info N/A
Overall Width (min. tread)	in.	67.3	Info N/A
Overall Height (top of ROPS)	in.	101	Info N/A
Weight (inc. std. tires and ROPS)	lbs.	3902(HST), 4233(HSTC)	3702
Min. Ground Clearance	in.	15.7	Info N/A
Transmission / Drive Train			
Transmission		Hydrostatic	Hydrostatic
Manual Speeds		3 Range Hydro	3 Range Hydro
Hydrostactic Transmission Functions		Load Sensing, Hi/Lo, Response Control, Auto-Throttle	Load Sensing, Response Control
Brakes		Multiple Wet Disc	Wet Disc
Clutch Diamter	in.	9.4	Info N/A
Clutch		Dry Type - Single Stage	Wet Disc



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L5240	JOHN DEERE 4520
PTO System			
Type		Independent	Independent
Rear PTO	RPM	540	540
Mid PTO	RPM	Optional 2000	Optional 2100
Hydraulic System / 3-Point Hitch			
Hitch Category (SAE)		Category I and II	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only
Pump Capacity (Main/PS)	gpm	9.8 / 4.9	12 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2980	2500
Steering		Hydrostatic	Power
Standard Tires			
Front Tire		9.5-16	8-16
Rear Tire		14.9-26	13.6-28



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L5240	JOHN DEERE 4520
Other Specifications			
Deck		Flat	Flat
Min. Turning Radius	ft.	9.2	9.2
Width Between Fenders	in.	31.5	31.5
Cruise Control		Standard	Standard
Alternator	amps	45 (55 on Cab Models)	75
Rear Differential Lock		Standard	Standard
Entry/Exit Step		Standard	Standard
Drawbar		Adj. Drawbar Std / Swinging Optional	Adjustable Drawbar
Foldable ROPS		Standard	Standard
Tilt Steering Wheel		Standard	Standard
Tool Box		Standard	Standard
Cup Holder		Standard	Standard
Deluxe Seat with Armrests		Standard	Armrests Optional
Reclining Seat		Standard	N/A
Kubota Intellipanel		Standard	N/A
Rubber Mat		Standard	Standard
Underhood Muffler		Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.



COMPARISON

FEATURE		KUBOTA L5740	JOHN DEERE 4720
Engine			
Engine Manufacturer/Model		Kubota	JD (Mexico)
Gross Horsepower	HP	59	Info N/A
PTO Horsepower	HP	50	50
Rated Speed	RPM	2700	2400
No. Cylinders/Displacement	cu. in.	4 / 148.5	4 / 149
Fuel Tank Capacity	gal.	14.3	14.5
Air Cleaner		Dual Element	Dual Element
Dimensions			
Wheelbase	in.	75.4	71.5
Overall Length (w/out 3-pt hitch)	in.	126.4	Info N/A
Overall Width (min. tread)	in.	67.3	Info N/A
Overall Height (top of ROPS)	in.	101	Info N/A
Weight (inc. std. tires and ROPS)	lbs.	3902(HST), 4233(HSTC)	3702
Min. Ground Clearance	in.	15.7	Info N/A
Transmission / Drive Train			
Transmission		Hydrostatic	Hydrostatic
Manual Speeds		3 Range Hydro	3 Range Hydro
Hydrostactic Transmission Functions		Load Sensing, Hi/Lo, Response Control, Auto-Throttle	Load Sensing, Response Control
Brakes		Multiple Wet Disc	Wet Disc
Clutch Diameter	in.	9.4	Info N/A
Clutch		Dry Type - Single Stage	Wet Disc



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L5740	JOHN DEERE 4720
PTO System			
Type		Independent	Independent
Rear PTO	RPM	540	540
Mid PTO	RPM	Optional 2000	Optional 2100
Hydraulic System / 3-Point Hitch			
Hitch Category (SAE)		Category I and II	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only
Pump Capacity (Main/PS)	gpm	9.8 / 4.9	12 / 5.1
Lift Capacity at 24" Behind L.P.	lbs.	2980	2500
Steering		Hydrostatic	Power
Standard Tires			
Front Tire		9.5-16	8-16
Rear Tire		14.9-26	13.6-28



Compact Tractors

L3240/L3540/L3940/L4240/L4740/L5040/L5240/L5740



COMPARISON

FEATURE		KUBOTA L5740	JOHN DEERE 4720
Other Specifications			
Deck		Flat	Flat
Min. Turning Radius	ft.	9.2	9.2
Width Between Fenders	in.	31.5	31.5
Cruise Control		Standard	Standard
Alternator	amps	45 (55 on Cab Models)	75
Rear Differential Lock		Standard	Standard
Entry/Exit Step		Standard	Standard
Drawbar		Adj. Drawbar Std / Swinging Optional	Adjustable Drawbar
Foldable ROPS		Standard	Standard
Tilt Steering Wheel		Standard	Standard
Tool Box		Standard	Standard
Cup Holder		Standard	Standard
Deluxe Seat with Armrests		Standard	Armrests Optional
Reclining Seat		Standard	N/A
Kubota Intellipanel		Standard	N/A
Rubber Mat		Standard	Standard
Underhood Muffler		Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.