

B2301 - B2601

COMPETITIVE COMPARISON						
MODEL		Kubota B2301	Kubota B2601	John Deere 2025R	Mahindra Max 24 HST	Mahindra Max 26XL HST
Engine	Manufacturer	Kubota	Kubota	Yanmar	Mahindra	Mahindra
	Type	Diesel	Diesel	Diesel	Diesel	Diesel
	Gross Engine (*SAE J1995) HP (kw)	22 (16.4)*	25.5 (19.0)*	23.9 (17.8)	24.4 (18.2)	25.6 (19.1)
	PTO (*OECD 2) HP (kw)	17.5 (13.0)*	19.5 (14.5)*	18.0 (14.5)	19.5 (14.4)	20 (14.9)
	Rated Engine Speed rpm	2800	2800	3000	2500	2600
	Cylinders/Displacement cu.in. (liters)	3 / 61.1 (1.001)	3 / 68.5 (1.123)	3 / 77.3 (1.267)	3 / 80.4 (1.318)	3 / 80.4 (1.318)
	Engine Torque @ rated speed ft./lb. (N/m)	45.6 (6.30)	53.4 (7.38)	40.27 (54.6)	-	-
	Fuel Tank Cap US Gal. (L)	6.1 (23)	6.1 (23)	6.1 (23)	6.1 (23)	6.1 (23)
Electrical	Battery Size (CCA)	430	430	500	46AH	35AH
	Alternator (12 volt, amp)	14.5 Amp dynamo	14.5 Amp dynamo	40	50	50
Transmission	Transmission	Hydrostatic - 3 Range	Hydrostatic - 3 Range	Hydrostatic - 2 Range	Hydrostatic - 2 Range	Hydrostatic - 2 Range
	Brakes	Multi Wet Disc	Multi Wet Disc	Wet Disc	Wet Disc	Wet Disc
	Steering	Power	Power	Power	Power	Power
	Axle Capacity Front, lb. (kg) Rear, lb. (kg)	1323 (600) 1764 (800)	1323 (600) 1764 (800)	1940 (880) 2426 (1100)	- -	- -
Hydraulics	Remote Control Valves Available	3, Optional	3, Optional	2, Optional	1, Optional	1, Optional
	Main Pump Flow gpm (l/m)	4.7 (17.9)	4.7 (17.9)	3.4 (12.7)	4.6	5.8
	Total Flow GPM gpm (l/m)	8.3 (31.4)	8.3 (31.4)	5.6 (21.2)	7.3	8.5
	Control Type	Position	Position	Position	Position	Position
3-point Hitch	Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
	Lower Link Adjustment	Check Chains	Check Chains	Check chains	Check Chains	Check Chains
	Lift Capacity (24-in. behind link arms) lb. (kg)	1411 (640)	1411 (640)	1150 (522)	-	-
	Lift Capacity @ lift links ends lb. (kg)	1808 (820)	1808 (820)	N/P	1400	2205
Power Take-Off (PTO)	Standard	Rear 540 / Mid 2500	Rear 540 / Mid 2500	Rear 540 / Mid 2100	Rear 540 / Mid 2556	Rear 540 / Mid 2526
	Control	Independent	Independent	Independent	Live	Live
	Clutch	-	-	-	-	-

B2301 - B2601

COMPETITIVE COMPARISON							
MODEL		Kubota B2301	Kubota B2601	John Deere 2025R	Mahindra Max 24 HST	Mahindra Max 26XL HST	
Dimensions	Wheelbase	in. (mm)	61.4 (1560)	61.4 (1560)	63 (1600)	-	-
	Height	in. (mm)	83.9 (2130)	85.0 (2160)	-	81.5 (2070)	84.3 (2140)
	Front Tread	in. (mm)	32.7 (830)	33.5 (850)	36.3 (923)	-	-
	Min. ground clearance	in. (mm)	12.0 (305)	12.8 (325)	13 (330)	-	-
	Turning Radius w/ Brake	ft (m)	6.9 (2.1)	6.9 (2.1)	6.7 (2.0)	7.2 (2.2)	6.6 (2.0)
	Tractor Weight	lb (kg)	1566 (710)	1632 (740)	1660 (753)	1693 (767.9)	1863 (845)
Standard Tires	Front		6-12 ; Ag	7-12 ; Ag	23x8.50-12 ; Industrial	20x8-10 ; Industrial	23x8.5-12 ; Industrial
	Rear		9.5-16 ; Ag	11.2-16 ; Ag	12-16.5 ; Industrial	27x12.5-15 ; Industrial	12x16.5 ; Industrial

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.