

PUSH MORE. PULL MORE. LIFT MORE.
With a Mahindra Tractor

Mahindra
RISE.

5010 CAB 4WD HST [50HP] / 6110 CAB 4WD SHUTTLE [60HP]

MAHINDRA 5010/6110 CAB 4WD TRACTORS



FOR MORE INFORMATION ON MAHINDRA

PH TOLL FREE: 1800 45 95 75 (WITHIN AUSTRALIA)

OR VISIT OUR COMPREHENSIVE WEBSITE

Photographs may show overseas models or illustrate non standard equipment. Please read your Mahindra Tractor manual carefully prior to operation.
^3 year engine and powertrain warranty. #Mahindra & Mahindra Ltd is the No1 Tractor company in the world by volume.

No.1 TRACTOR
COMPANY
IN THE WORLD
BY VOLUME

 **FIND US ON FACEBOOK**
[FACEBOOK.MAHINDRAAG.COM.AU](https://www.facebook.com/mahindraag.com.au)

 **JAPAN
QUALITY
MEDAL
WINNER**

**FREE 3 YEAR
WARRANTY**

FOR MORE INFORMATION ON MAHINDRA PRODUCTS, VISIT:
WWW.MAHINDRA.COM.AU 

5010 CAB 4WD HST [50HP] Wow, unbelievable! A 50 horsepower tractor with air-conditioning and heated cabin at such an affordable price.

With the ease of operation that HST provides and the simply amazing visibility in this cabin design, customers will be able to work in the evenings, early mornings, rain showers, cold winters, hot summers and inclement seasonal regions of our wide brown land.

If you ever wanted the features of a big tractor, but the price and flexibility of a small tractor then this tractor is for you. Simply put the best value cabin tractor on the market with the ease of operation that hydrostatic provides.

5010 4WD [50HP] FEATURES:

- Great value 4 cylinder 50HP CAB
- Hydrostatic Transmission
- Air conditioning and heating standard
- Agricultural tyres standard
- Tractor weight 1850kgs
- Dimensions: length 3208mm x width 1591mm

6110 CAB 4WD SHUTTLE [60HP] 60 horsepower in a cabin tractor with air-conditioning and heating enables working all year round in all climate conditions. The 6110 Shuttle Cab features Synchro-shuttle with 12 forward and 12 reverse speeds, and a 1600 kgs hydraulic lift capacity on the linkage. New standard features on all 10 series Cab models include ergonomic and spacious cabs with flat operator's station for comfort. Standard features on the 6110 include one remote valve, tilt steering wheel and a suspension seat.

The 10 series offers heavy-duty performance at a no-nonsense price. The fuel-efficient engines will help you reduce your operating costs and save money with the value-pricing of these new models.

6110 4WD [60HP] FEATURES:

- 12F + 12R Synchro Shuttle
- 1600kgs lift capacity on linkage
- Air conditioning and heating standard
- Agricultural tyres standard
- Tractor weight 2200kgs
- Dimensions: length 3590mm x width 1817mm

Suspension Seat



Rear Lighting Package



Synchro Shuttle Lever



Telescopic Lower Links on 6110



TRACTOR SPECIFICATIONS

ENGINE	5010 4WD	6110 4WD
Type	Indirect Fuel Injection	Fuel Injected Turbo Diesel
Cylinders	4	4
Displacement cc	2435	2435
Engine HP (kW) @ rpm	50 @ 2600	60 @ 2600
TRANSMISSION		
Type	HST	Gear
Number of Gears	Infinite/3 Range	12 F/12 R
CLUTCH		
Type	Not applicable	Dry
BRAKES		
Type	Wet Disc	Wet Disc
HYDRAULICS AND LINKAGES		
Type	Dual Gear Pump	Dual Gear Pump
Max Lifting Capacity (Kgs)	1503	1600
Implement Pump Flow	36.6 lpm	41.6 lpm
Three Point Linkage	Cat 1	Cat 2
Auxiliary Remotes	1 Standard	1 Standard
PTO		
PTO Type	Independent with Electric-hydraulic engagement	Independent with Electric-hydraulic engagement
Max PTO HP	41.7	48.5
PTO RPM	540	540
GROUND CLEARANCE		
Min. Ground Clearance (mm)	350	455
STEERING		
Steering Type	Hydrostatic / Tilttable	Hydrostatic / Tilttable
OPERATING WEIGHT		
Total (Kgs)	1850	2200
DIMENSIONS		
Overall Length (mm)	3208	3590
Overall Width	1591	1817
Turning Radius with Brakes (mm)	3352	3815
TYRES		
Ag (Front/Rear)	9.5 x 16/14.9 x 24 Standard	9.5 x 20/14.9 x 28 Standard

LOADER SPECIFICATIONS

LOADER	ML501	ML611
TRACTOR MODEL	5010 4WD	6010 4WD
Self Level Mechanism	Yes	Yes
Maximum Lift Height	2932 mm	2932 mm
Clearance Attachment Level	2670 mm	2670 mm
Clearance Attachment Dumped	2091 mm	2091 mm
Reach at Maximum Height	583 mm	543 mm
Maximum Dump Angle	69°	69°
Reach with Attachment on Ground	2001 mm	1912 mm
Attachment Rollback Angle	39°	39°
Digging Depth Below Grade	131 mm	131 mm
Overall Height Carry Position	1689 mm	1689 mm
Depth of Attachment (to back of inner shell)	579 mm	579 mm
Height Attachment	563 mm	563 mm
Depth Attachment (to pivot pin)	801 mm	801 mm
Lift Capacity Full Height Pivot Pins	1416 kgf	1416 kgf
Breakout Force Ground Level, Pivot Pins	2370 kgf	2370 kgf
Relief Valve Setting (Loader Control Valve)	175 kg/cm ²	175 kg/cm ²
Attachment used for specification	1830 mm	1830 mm
Bucket Capacity	0.318 cu.m	0.363 cu.m
Hydraulic System	Tractor pump with loader control valve	Tractor pump with loader control valve
Bucket Level indicator	Standard	Standard
Optional Attachments	Grill guard, bale spikes, pallet forks and 4-in-1 buckets	Grill guard, bale spikes, pallet forks and 4-in-1 buckets

Dealer Details:

