



3-point Linkage

Mahindra employs 3-point linkages that are heavy and sturdy to ensure stability and safety. Compare ours to other brands and you can see the difference.

Front Axle

Mahindra insists on using bigger, thicker, stronger axles to achieve maximum stability.

Reinforced Fenders

Our fenders are reinforced and use a thicker gauge of sheet metal for strength and durability.

Mahindra 10 Series



Forward-Reverse Synchro-Shuttle with 12 forward / 12 reverse gears

Hydraulics with both position and draft controls

Ergonomic design places controls within easy operator reach

Foldable ROPS

Designed for easy maintenance

Higher lift capacity

Safety glass at front of platform for clear visibility and as mud-guard for front tires

Flat platform for easy access

Independent PTO with safety mechanism and electro-hydraulic clutch

SUPERIOR PERFORMANCE

Higher lift capacity

Handle larger implements
Get work done a lot faster

Heavy-duty components

Tough and rugged
Keep right on performing day after day

Sturdier chassis

Greater stability
Keeps you safe while handling rigorous work

Heavier chassis

Additional weight provides extra traction

Standard Features

- Forward-Reverse Synchro-Shuttle with 12 forward / 12 reverse gears
- Independent PTO with safety mechanism & electro-hydraulic clutch
- Easy access PTO on/off switch
- Differential lock
- Tiltable steering column with 3 positions
- Hydraulics with both position and draft controls
- One set of auxiliary remote hydraulic valves
- Hitch lowering speed adjustment knob
- Telescopic check chains for lower links
- Choice of Ag, Industrial, Turf tires at no extra cost
- Choice of Ag, Industrial, Turf or golf tires
- Spacious, full-flat operator platform with rubber mat
- Enclosed down-swept exhaust muffler
- Comfortable suspension seat with retractable seat belt, arm rests and rainwater drain facility
- Seat can be adjusted to suit the operator weight and back angle for added comfort, for smooth ride
- Sleek, powerful headlamps and stylish front grille
- Hood opens completely for ease of access
- Reinforced metal fenders with sleek plastic mudguards
- Full foldable ROPS
- Electrical power socket at tractor rear for external connections
- Rear work light
- Adjustable drawbar
- Front bumper / weight bracket
- Clear view, multifunctional instrument panel
- Easy hook for top link retention
- Comfortable mounting step and easy grip handle on either side of tractor
- Easy grip, comfortable levers / handles
- Ergonomic controls and pedals for operator comfort
- Flexible plastic cover for ignition switch protection
- Handy toolbox in the operator platform (under rubber mat)
- Easy latch for clutch pedal locking during tractor storage
- Safety glass at front of platform for clear visibility and as mud-guard for front tires
- 3-year limited warranty*

MAHINDRA

10 SERIES



Cultivate your dreams®



The Mahindra Group Mahindra USA, Inc.
17723 FM 2920, Tomball, Texas 77377
1-800-887-2286 www.mahindrausa.com

*3-year engine and power train warranty — see dealer for details.
Specifications and design subject to change without notice. ©2007 Mahindra USA, MAH-0507
The Mahindra Group ©2007 Mahindra USA, Inc.

THE 10 SERIES: VERSATILE, HEAVY-DUTY, COMPACT 4WD TRACTORS ARE EQUIPPED WITH AN ABUNDANCE OF STANDARD FEATURES.

Mahindra tractors are built for superior performance. Every tractor is designed and manufactured to help you get the most out of your land. So you can cultivate your dreams. The 10 Series is no exception. These modern-looking workhorses are available in 34 hp and 40 hp 4WD.

Mahindra tractors consistently outperform others in their class by being heavier and more durable — yet easy to handle. Their rugged, cast-iron chassis give the tractors extra weight, providing more traction, stability and control.

Our tractors have higher lift capacities. Carry bigger loads. Handle larger implements.

A Mahindra tractor does what needs to be done — quickly and efficiently.

Customer satisfaction

Who can gauge our commitment to product quality better than the people who own our tractors? In a recent study, a leading market research firm interviewed Mahindra owners nationwide and asked

them to evaluate their level of satisfaction with the performance of their Mahindra tractors. The study found that 98% of Mahindra owners were likely to recommend Mahindra to their friends and family.

98%
OF MAHINDRA OWNERS
ARE LIKELY TO
RECOMMEND
MAHINDRA

A dealer network as sturdy and stable as the tractors they sell

Mahindra dealers are fully qualified and armed with the resources to not only put you

on the right tractor, but to continue to meet your needs after your purchase. We support our dealers with the ability to ship parts within 24 hours. We provide them with warranty assistance, technical support, low-rate retail financing and on-site approvals, making it quicker and easier to put you on the tractor of your choice.

Cultivating dreams in the U.S.

From army vehicles to farm tractors to major automobile manufacturing, Mahindra's relationship with American

industry goes back to World War II — when our parent company, Mahindra & Mahindra, assembled the famous Willys Jeep for American GIs.

After teaming up with International Harvester in 1963 to manufacture tractors, M&M today ranks among the largest tractor companies in the world, with sales of nearly 85,000 units annually in 10 countries.

The Farm Equipment Sector of Mahindra & Mahindra Ltd. received the coveted Deming Application Prize for 2003 — considered the Nobel Prize for manufacturing, for establishing Total Quality Management in all business operations. Mahindra & Mahindra Ltd. is the only tractor company in the world to achieve this honor.

3-YEAR WARRANTY*

Mahindra USA's Tomball, Texas facility was joined by a second assembly and distribution center in Calhoun, Georgia, 68 miles north of Atlanta — more than doubling our production capacity to meet growing demands for our tractors.



Grille Guard
Protect your nose from those annoying dents and dings that often occur during the course of a hard day's work.



Quick Attach Adapter
This well-designed feature makes swapping out implements a snap, so you can spend less time assembling and more time getting your work done.



Loader
Whether moving earth, scraping a surface or smoothing a gravel road, Mahindra's loader is a rugged and extremely versatile tool.



Pallet Fork
This solid metal implement is a convenient tool to have on hand. Combined with Mahindra's outstanding lift capacity, the pallet fork will help you move all kinds of loads.

TRACTORS	3510	4110
Engine	3A165	4A200
Type	Four stroke, indirect injection, water-cooled, diesel	Four stroke, indirect injection, water-cooled, diesel
Cylinders	3	4
Engine HP (kW) @ rpm	34 (25.3) @ 2700	40.4 (30.1) @ 2700
Compression Ratio	22:1	22:1
Displacement cubic inch (cc)	100.3 (1648)	122 (2000)
Electrical		
Battery Capacity	12 volt, 110 amp hours	12 volt, 110 amp hours
Alternator	12 volt, 50 amps	12 volt, 50 amps
Clutch		
Type	Single plate, dry	Single plate, dry
Transmission		
Type	Forward-Reverse Synchro-Shuttle with partial synchromesh	Forward-Reverse Synchro-Shuttle with partial synchromesh
Number of Gears/Speeds	12 forward, 12 reverse	12 forward, 12 reverse
Front Wheel Drive		
Type	Mechanical	Mechanical
Steering		
Type	Hydrostatic power	Hydrostatic power
Pump Output (gallons per minute)	3.3	4.4
Brakes		
Type	Wet disc	Wet disc
Hydraulic System		
Type	Open center, full-live hydraulic with position and draft controls	Open center, full-live hydraulic with position and draft controls
Pump Output (gallons per minute)	7.9	9.5
3-Point Linkage	Category 1, with check chains	Category 1, with check chains
Lift Capacity (lbs.)	2865	2865
Rear Auxiliary Remote Valves	1 standard	1 standard
PTO		
Type	Independent PTO with safety mechanism and electro-hydraulic clutch	Independent PTO with safety mechanism and electro-hydraulic clutch
PTO RPM (engine rpm)	540 @ 2522 / 1000 @ 2866	540 @ 2524 / 1000 @ 2866
PTO HP (kW)	28.7 (21.4)	33.6 (25.1)
Operating Weight		
Total (lbs.)	3483	3969
Dimensions with Industrial Tires		
Overall Length Inches (mm)	127 (3225)	139 (3531)
Overall Width Inches (mm)	66.9 (1700)	71.2 (1808)
Turning Radius Min. Feet (mts)	8.2 (2.5)	10.2 (3.1)
Tires Sizes and Options		
Ag (Front / Rear)	8x16 / 12.4x24	9.5x16 / 14.9x24
Industrial (Front / Rear)	28x8.5-15 / 43x16-20	12x16.5 / 16.9x24
Turf (Front / Rear)	27x8.5-15 / 41x14-20	12x16.5 / 16.9x24
Options		
Soft Cab with Canopy	✓	✓
Snow Blowers	✓	✓

LOADER	ML112
Tractor Models	3510/4110
Maximum Lift Height	109.6"
Clearance with Attachment Dumped	89.8"
Reach at Maximum Height	26.4"
Maximum Dump Angle	52°
Attachment Rollback Angle	20°
Digging Depth Below Grade	7.1"
Lift Capacity to Full Height @ Pivot Pins	1972 lbs.
Breakout Force @ Pivot Pins	3343 lbs.
Rated Flow (Tractor System)	7.9 / 9.5 gpm
Attachment Width used for specification	72"
Attachment Rated Capacity used for specification	14.0 cu. ft.
Cycle Times @ rpm	2500 rpm
Raise Boom (seconds)	5.1 / 4.2
Lower Boom (seconds)	3.0 / 2.5
Dump Attachment (seconds)	4.2 / 3.5
Retract Attachment (seconds)	2.6 / 2.1
Optional Attachments	
Grille Guard (with or without loader)	✓
Quick Attach Adapter – Pin-On	✓
Pallet Fork	✓
Bale Spear	✓
Skid Steer Attachments	
Bucket	✓
Quick Attach Adapter	✓
Pallet Fork	✓
Bale Spear	✓

Sub-frame mounted backhoes also available.