HP/kW
65/48.5

MF425 Xtra

Simple yet powerful machinery from Massey Ferguson
Available in 2- and 4-Wheel Drive

VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

MASSEY FERGUSON

Specifications

Performance		MF 425 Xtra
Max Hp (kW) power	✪ ISO hp (kW)	65 (48.5)
Max Torque	@ 1400 rpm	235
Rated engine speed		2200
Engine		
Engine type		A4-3.9
No. of Cylinders		4
Capacity	cc	3900
Aspiration		Natural
Transmission		
8 x 2 Centre shift		●
12 x 4 Side shift		❍
Power take off		
Live single speed - 540 rpm		●
IPTO Single speed - 540 rpm		❍
Steering		
Hydrostatic		●
Hydraulics		
3-point linkage control		Mechanical
Lift capacity	max kgf	2500
Oil flow	litres/min	17
System pressure	bar	210
Auxiliary hydraulics		
Oil flow	litres/min	42
System pressure	bar	170
Spool valves		
		● 1
Brakes		
Type		Oil immersed
Standard wheels and tyres		
Front 2wd/4wd		7.50-16/12.4-24
Rear		18.4-30
Weights and Dimensions		
Weight without Ballast	kg	2870
Length	mm	4130
Height over exhaust	mm	2580
Wheelbase	mm	2370
Capacities		
Fuel tank	litres	100
Engine oil	litres	7
Transmission oil	litres	42

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

● = Standard
❍ = Optional
– = Not applicable/ available
✪ = ISO TR14396

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

AGCO Your Agriculture Company

MASSEY FERGUSON is a worldwide brand of AGCO.
© AGCO Limited. 2010 | A-B-English/15073/1010

MASSEY FERGUSON

HP/kW
72/53.7

MF435 Xtra

Simple yet powerful machinery from Massey Ferguson
Available in 2- and 4-Wheel Drive

VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

MASSEY FERGUSON

Specifications

Performance		MF 435 Xtra
Max Hp (kW) power	✪ ISO hp (kW)	72 (53.7)
Max Torque	@ 1400 rpm	267
Rated engine speed		2200
Engine		
Engine type		A4-4.1
No. of Cylinders		4
Capacity	cc	4100
Aspiration		Natural
Transmission		
8 x 2 Centre shift		●
12 x 4 Side shift		❍
Power take off		
Live single speed - 540 rpm		●
IPTO Single speed 540 rpm		❍
Steering		
Hydrostatic		●
Hydraulics		
3-point linkage control		Mechanical
Lift capacity	max kgf	2500
Oil flow	litres/min	17
System pressure	bar	210
Auxiliary hydraulics		
Oil flow	litres/min	42
System pressure	bar	170
Spool valves		
		● 1
Brakes		
Type		Oil immersed
Standard wheels and tyres		
Front 2wd/4wd		7.50-16/12.4-24
Rear		18.4-30
Weights and Dimensions		
Weight without Ballast	kg	2870
Length	mm	4130
Height over exhaust	mm	2580
Wheelbase	mm	2370
Capacities		
Fuel tank	litres	100
Engine oil	litres	8
Transmission oil	litres	42

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

● = Standard
❍ = Optional
– = Not applicable/ available
✪ = ISO TR14396

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

AGCO Your Agriculture Company

MASSEY FERGUSON is a worldwide brand of AGCO.
© AGCO Limited. 2010 | A-B-English/15074/1010

MASSEY FERGUSON

HP/kW
82/61.1

MF440 Xtra

Simple yet powerful machinery from Massey Ferguson
Available in 2- and 4-Wheel Drive, Cab and Platform

VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

MASSEY FERGUSON

Specifications

Performance		MF 440 Xtra
Max Hp (kW) power	✪ ISO hp (kW)	82 (61.1)
Max Torque	@ 1400 rpm	288
Rated engine speed		2200
Engine		
Engine type		A4-4.1
No. of Cylinders		4
Capacity	cc	4100
Aspiration		Natural
Transmission		
8 x 2 Centre shift		●
12 x 4 Side shift	Cab/Platform	●/❍
Power take off		
Live single speed - 540 rpm		●
IPTO Single speed - 540 rpm	Cab/Platform	●/❍
Steering		
Hydrostatic		●
Hydraulics		
3-point linkage control		Mechanical
Lift capacity	max kgf	2500
Oil flow	litres/min	17
System pressure	bar	210
Auxiliary hydraulics		
Oil flow	litres/min	42
System pressure	bar	170
Spool valves		
	Cab/Platform	● 2 valves / ● 1 valve
Brakes		
Type		Oil immersed
Standard wheels and tyres		
Front 2wd/4wd		7.50-16/12.4-24
Rear		18.4-30
Weights and Dimensions		
Weight without Ballast Cab/Platform	kg	3430/3040
Length	mm	4130
Height over exhaust	mm	2580
Wheelbase	mm	2370
Capacities		
Fuel tank	litres	100
Engine oil	litres	8
Transmission oil	litres	42

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

● = Standard
❍ = Optional
– = Not applicable/ available
✪ = ISO TR14396

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

AGCO Your Agriculture Company
MASSEY FERGUSON is a worldwide brand of AGCO.
© AGCO Limited. 2010 | A-B-English/15075/1010

MASSEY FERGUSON

HP/kW
100/74

MF455 Xtra

Simple yet powerful machinery from Massey Ferguson
Available in 2- and 4-Wheel Drive, Cab and Platform

VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

MASSEY FERGUSON

Specifications

Performance		MF 455 Xtra
Max Hp (kW) power	✪ ISO hp (kW)	100 (74)
Max Torque	@ 1400 rpm	415
Rated engine speed		2200
Engine		
Engine type		1104.4C
No. of Cylinders		4
Capacity	cc	4400
Aspiration		Turbo
Transmission		
12 x 4 Side shift		●
Power take off		
Live single speed- 540 rpm		●
IPTO Single speed - 540 rpm	Cab/Platform	●/❍
IPTO Two Speed - 540/1000 rpm		❍
Steering		
Hydrostatic		●
Hydraulics		
3-point linkage control		Mechanical
Lift capacity	max kgf	2500
Oil flow	litres/min	17
System pressure	bar	210
Auxiliary hydraulics		
Oil flow	litres/min	42
System pressure	bar	170
Spool valves		
	Cab/Platform	● 2 valves/● 1 valve
Brakes		
Type		Oil immersed
Standard wheels and tyres		
Front 2wd/4wd		9.00-16/14.9-24
Rear		18.4-34
Weights and Dimensions		
Weight without Ballast Cab/Platform	kg	4460/4070
Length	mm	4270
Height over exhaust	mm	2640
Wheelbase	mm	2370
Capacities		
Fuel tank	litres	100
Engine oil	litres	8
Transmission oil	litres	46

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

● = Standard
❍ = Optional
– = Not applicable/ available
✪ = ISO TR14396

AGCO Your Agriculture Company

MASSEY FERGUSON is a worldwide brand of AGCO.
© AGCO Limited. 2010 | A-B-English/15076/1110

MASSEY FERGUSON

HP/kW
110/81.4

MF460 Xtra

Simple yet powerful machinery from Massey Ferguson
4-Wheel Drive, Cab and Platform tractors

VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

MASSEY FERGUSON

Specifications

Performance		MF 460 Xtra
Max Hp (kW) power	✪ ISO hp (kW)	110 (81.4)
Max Torque	@ 1400 rpm	425
Rated engine speed		2200
Engine		
Engine type		420DS
No. of Cylinders		4
Capacity	cc	4400
Aspiration		Turbo
Transmission		
12 x 4 Side shift		●
Power take off		
Live single speed - 540 rpm		●
IPTO Single speed - 540 rpm	Cab/Platform	●/❍
IPTO Two Speed - 540/1000 rpm		❍
Steering		
Hydrostatic		●
Hydraulics		
3-point linkage control		Mechanical
Lift capacity	max kgf	3800
Oil flow	litres/min	17
System pressure	bar	210
Auxiliary hydraulics		
Oil flow	litres/min	42
System pressure	bar	170
Spool valves		
	Cab/Platform	● 2 valves/ ● 1 valve
Brakes		
Type		Oil immersed
Standard wheels and tyres		
4wd		14.9-24
Rear		18.4-34
Weights and Dimensions		
Weight without Ballast Cab/Platform	kg	4600/4210
Length	mm	4470
Height over exhaust	mm	2640
Wheelbase	mm	2570
Capacities		
Fuel tank	litres	200
Engine oil	litres	15
Transmission oil	litres	46

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

● = Standard
❍ = Optional
– = Not applicable/ available
✪ = ISO TR14396

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

AGCO Your Agriculture Company

MASSEY FERGUSON is a worldwide brand of AGCO.
© AGCO Limited. 2010 | A-B-English/15077/1110

MASSEY FERGUSON

HP/kW
120/89.5

MF470 Xtra

Simple yet powerful machinery from Massey Ferguson
4-Wheel Drive, Cab and Platform tractors

VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

MASSEY FERGUSON

Specifications

Performance		MF 470 Xtra
Max Hp (kW) power	✪ ISO hp (kW)	120 (89.5)
Max Torque	@ 1400 rpm	470
Rated engine speed		2200
Engine		
Engine type		420DS
No. of Cylinders		4
Capacity	cc	4400
Aspiration		Turbo
Transmission		
12 x 4 Side shift		●
Power take off		
Live single speed - 540 rpm		●
IPTO Single speed - 540 rpm	Cab/Platform	●/❍
IPTO Two Speed - 540/1000 rpm		❍
Steering		
Hydrostatic		●
Hydraulics		
3-point linkage control		Mechanical
Lift capacity	max kgf	3800
Oil flow	litres/min	17
System pressure	bar	210
Auxiliary hydraulics		
Oil flow	litres/min	42
System pressure	bar	170
Spool valves		
	Cab/Platform	● 2 valves/ ● 1 valve
Brakes		
Type		Oil immersed
Standard wheels and tyres		
4wd		14.9-24
Rear		18.4-34
Weights and Dimensions		
Weight without Ballast Cab/Platform	kg	4600/4210
Length	mm	4630
Height over exhaust	mm	2640
Wheelbase	mm	2730
Capacities		
Fuel tank	litres	200
Engine oil	litres	15
Transmission oil	litres	46

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

● = Standard
❍ = Optional
– = Not applicable/ available
✪ = ISO TR14396

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

AGCO Your Agriculture Company
MASSEY FERGUSON is a worldwide brand of AGCO.
© AGCO Limited. 2010 | A-B-English/15078/1010

MASSEY FERGUSON

HP/kW
130/96.5

MF480 Xtra

Simple yet powerful machinery from Massey Ferguson
4-Wheel Drive, Cab and Platform tractors

VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

MASSEY FERGUSON

Specifications

Performance		MF 480 Xtra
Max Hp (kW) power	✪ ISO hp (kW)	130 (96.5)
Max Torque	@ 1400 rpm	525
Rated engine speed		2200
Engine		
Engine type		420DS
No. of Cylinders		4
Capacity	cc	4400
Aspiration		Turbo
Transmission		
12 x 4 Side shift		●
Power take off		
Live single speed - 540 rpm		●
IPTO Single speed - 540 rpm	Cab/Platform	●/❍
IPTO Two Speed - 540/1000 rpm		❍
Steering		
Hydrostatic		●
Hydraulics		
3-point linkage control		Mechanical
Lift capacity	max kgf	3800
Oil flow	litres/min	17
System pressure	bar	210
Auxiliary hydraulics		
Oil flow	litres/min	42
System pressure	bar	170
Spool valves		
	Cab/Platform	● 2 valves / ● 1 valve
Brakes		
Type		Oil immersed
Standard wheels and tyres		
4wd		14.9-24
Rear		18.4-34
Weights and Dimensions		
Weight without Ballast Cab/Platform	kg	4600/4210
Length	mm	4630
Height over exhaust	mm	2640
Wheelbase	mm	2730
Capacities		
Fuel tank	litres	200
Engine oil	litres	15
Transmission oil	litres	46

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

● = Standard
❍ = Optional
– = Not applicable/ available
✪ = ISO TR14396

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

AGCO Your Agriculture Company
MASSEY FERGUSON is a worldwide brand of AGCO.
© AGCO Limited. 2010 | A-B-English/15079/1010

MASSEY FERGUSON