



New!

NEW HOLLAND BOOMER™ 8N

To say you enjoy working outdoors is an understatement. The All-New, All-Classic New Holland Boomer™ 8N features the timeless look of the original 8N, but with the power of 50 horses, so you can load mulch, mow the lawn, clear a pasture, or complete many other outdoor tasks. With a padded seat, power steering and a single pedal to make it go, the Boomer 8N from New Holland is comfortable, easy and fun to drive, too.

EXPLORE
the **INSPIRATION**
BEHIND THE ALL NEW, ALL CLASSIC

boomer 8N

A LEGEND REBORN

New Holland has revived the much-loved 8N tractor into a newer, more powerful form that brings what you love about farming into the 21st Century. The Boomer 8N features innovations like a Continuously Variable Transmission that is driven like a car. And, the new padded seat, reminiscent of the original pan-style metal seat, is fully adjustable, soft and comfortable. Power steering, along with a tilt and telescoping steering wheel, make maneuvering a breeze.



SPECIFICATIONS

ENGINE

Engine Power	50 hp (37.3 kW)
Rated Engine Speed	2800 rpm
Cylinders	4
Displacement	135.2 cu in (2.2 L)
Aspiration	Natural
Axle Option	4WD

TRANSMISSION

Transmission Type	Continuously Variable Transmission (CVT)
PTO Horsepower	40.0 hp (30.1 kW)
Number of Forward / Reverse Speeds	Infinite up to 18.6 mph
Maximum Speed Forward	18.6 mph (30.0 kph)
Transmission Functionality	
Reactivity	Standard
Cruise Control	Standard
Anti-stall	Standard
Speed Set	Standard

PTO

PTO Type	Independent
Mid PTO available	Optional
PTO Clutch Type	Wet disc

HITCH FEATURES AND LIFT CAPACITY

3 point hitch Lift Capacity	2,800 lb (1270 kg)
Hitch Category	Category I
Flexible Link Ends	Standard
Telescopic Stabilizers	Standard
Drawbar – 2 position, swinging	Standard

FLUID CAPACITIES

Fuel Tank	13 gal (49.2 L)
Engine Oil with Filter	6.3 Qts (6.0 L)

HYDRAULIC SYSTEM

Hydraulic System Type	Open Center
System Pressure	2500 psi (172.4 bar)
Main Hydraulic Pump Type	Gear
Implement Pump Flow	10.5 (39.8 Lpm)
Powersteering Pump Flow	5.1 gpm (19.4 Lpm)

BRAKE SYSTEM

Brake Type	Wet disc
Brake Operation/Actuation	Mechanical Pedal
Brake Location	Right side, single pedal

PLATFORM

Operator Platform	Semi – Flat
Retro-style adjustable seat	Standard
Tilt, telescoping steering wheel	Standard
Power Steering	Standard
Foldable Rollbar	Standard
Left side control	Standard
Steps (2)	Standard
Grab rails (2)	Standard
Shuttle lever (left)	Standard
Type of Instrument Cluster	Analog and digital combo

LIGHTS (front end and fenders)

No. of Forward Lights	2
No. of Rear Lights	1 Opt

DIMENSIONS

Length, 4WD, with 3pt horizontal	122 in (3098 mm)
Minimum Width	68.3 in (1736 mm)
Overall Height – rollbar upright	97.4 in (2473 mm)
Wheelbase	73.5 in (1867 mm)
Ground Clearance - Drawbar	12.3 in (313 mm)

WEIGHT

Total Weight, 4WD w/ROPS	3,760 lb (1705 kg)
--------------------------	--------------------

AVAILABLE TIRE SIZE

Ag Size, 4WD Front	8.0x16 (R1)
Ag Size, Rear	14.9x24 (R1)
Ind Size, 4WD Front	10x16.5 (R4)
Ind Size, Rear	17.5x24 (R4)
Turf, 4WD Front	27x10.5-15 (R3)
Turf Size, Rear	44x18-20 (R3)

WARRANTY

Full Coverage	24 months or 2000 hours
Powertrain	36 months or 2000 hours

*Extended Warranty available

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.