

# T503 4WD CAB



T503 is a pleasure to operate and will suit mid-size farms and landscape applications. Fitted with a quiet 4-cylinder Perkins diesel engine that provides plenty of power and torque. Available in manual or hydrostatic transmission.



ENGINE



AIR-CONDITIONED CAB



ADJUSTABLE STEERING



LINKAGE ARMS

- Perkins engine
- Shuttle or HST transmission
- Push button PTO
- Air-conditioned cabin
- Flat operator's platform
- Integrated joystick control
- 3 Year warranty plan
- Front loader with 4-in-1 bucket – optional



QualityMade reflects the quality and generous features of the tractors built by TYM Korea for over 40 years. Experience a TYM Quality Made tractor at great value.



|                                                                          | T503 4WD CAB                      | T503 HST 4WD CAB                  |
|--------------------------------------------------------------------------|-----------------------------------|-----------------------------------|
| <b>Engine</b>                                                            | Perkins                           | Perkins                           |
| Engine model                                                             | 404D-22                           | 404D-22                           |
| Max Power HP/Kw                                                          | 50/37                             | 50/37                             |
| No. Cylinders                                                            | 4                                 | 4                                 |
| Fuel tank capacity                                                       | 60 litres                         | 60 litres                         |
| Cruise control                                                           | No                                | Yes                               |
| Engine load sensing                                                      | No                                | Yes                               |
| <b>Transmission</b>                                                      | Synchro                           | Hydrostatic                       |
| No. of speeds                                                            | 16Fx16R                           | Variable                          |
| No. of ranges                                                            | 4                                 | 3                                 |
| Max. Travelling speed                                                    | 33 km/h                           | 33 km/h                           |
| Shuttle                                                                  | Synchromesh                       | HST                               |
| Side by side HST pedals                                                  | No                                | Yes                               |
| HST pedal response control                                               | No                                | Yes                               |
| <b>PTO</b>                                                               |                                   |                                   |
| PTO type                                                                 | Independent                       | Independent                       |
| PTO control                                                              | Electrohydraulic                  | Electrohydraulic                  |
| PTO speed                                                                | 540 RPM                           | 540/1,000 RPM                     |
| Auto PTO                                                                 | Standard                          | Standard                          |
| <b>Hydraulics</b>                                                        |                                   |                                   |
| 3 Point Linkage Lift capacity                                            | 1,503kg                           | 1,503kg                           |
| 3 Point linkage category                                                 | 1                                 | 1                                 |
| Position draft control                                                   | Yes                               | Yes                               |
| Telescopic adjustable lower link arms                                    | Yes                               | Yes                               |
| Number of hydraulic remote outlets                                       | 2 sets                            | 2 sets                            |
| Hydraulic flow (L/min)                                                   | 36.5 + 19.2                       | 36.5 + 19.2                       |
| <b>Dimensions</b>                                                        |                                   |                                   |
| Length with 3P/L                                                         | 3590 mm                           | 3590 mm                           |
| Width (Variable)                                                         | 1620-1828 mm                      | 1620-1828 mm                      |
| Weight                                                                   | 1,900kg                           | 1,900kg                           |
| Ground Clearance Front Axle                                              | 410mm                             | 410mm                             |
| Height to cabin                                                          | 2,530mm                           | 2,530mm                           |
| Tyres                                                                    | Front (9.5 x 16) Rear (13.6 x 26) | Front (9.5 x 16) Rear (13.6 x 26) |
| Industrial tyres (optional)                                              | Front (12-16.5) Rear (17.5L-24)   | Front (12-16.5) Rear (17.5L-24)   |
| <b>Driving area</b>                                                      |                                   |                                   |
| Air-conditioned cabin                                                    | Yes                               | Yes                               |
| Roof hatch                                                               | Standard                          | Standard                          |
| Radio                                                                    | Yes                               | Yes                               |
| Adjustable steering column                                               | Yes                               | Yes                               |
| 4-in-1 loader with quick detach, euro hitch & integrated loader joystick | Optional                          | Optional                          |

L503C202407



For more information  
[tym-tractors.com.au](http://tym-tractors.com.au)