Since 1946
tractor is zetor

PROXIMA *PLUS*

85 ▪ 95 ▪ 105

Zetor

www.zetor.com

ZETOR PROXIMA PLUS

MODEL	UNITS	85	95	105
ENGINE				
Model		Zetor 1205	Zetor 1005	Zetor 1305
Homologated power 2000/25	kW/HP	64,3/87	70,4/96	78,4/107
Rated speed	rpm	2200		
No. of cylinders		4		
Aspiration		turbocharged		
Bore/Stroke	mm	105/120		
Displacement	cc	4156		
Torque reserve	%	35		
Emissions		TIER III		
CLUTCH				
Type		dry, single plate, hydraulic control		
Diameter	mm	310		
Lining		cerametallic		
TRANSMISSION				
Type		two-stage power shift		
Shifting		fully synchronised		
Gears forward/reverse		16/16		
Speed	kmph	30 and 40	40	
PTO SHAFT				
Type		live/ground speed, wet multi-plate PTO clutch		
Speeds	rpm	540/1000 (540/540E)		
Front PTO - speed	rpm	+1000 (–1000), optional		
HYDRAULICS				
Type		mechanical, top link draft sensing		
Three point linkage		category I and II		
Control		position, draft, mixed		
Lift capacity	kN	41.5		
Operating pressure	MPa	18		
Pump capacity	(l/min)	50		
SCV's		three set of remotes standard		
OTHER				
Drive system		4WD		
Operator's station		cab version		
Steering		hydrostatic		
Service brake		wet disc brake, hydraulic control		
Parking brake		mechanical control		
Front axle 4WD		Carraro 20.16, wet brakes in wheels		
Rear axle		differential lock engaged electro-pneumatically		
DIMENSIONS				
Lenght	mm	3670		
Width	mm	1910		
Height	mm	2718		
Wheel base	mm	2328		
Ground clearance	mm	402		
Standard front tyres		11,2-24		
Standard rear tyres		16,9-30		
Weight	kg	3740		
OPTIONAL				

- adjustable steering wheel
- A/C
- adjustable trailer hitch
- pick-up hitch
- Grammer air suspended seats
- passenger seat
- front and rear weights
- hydraulic or air trailer brakes
- choice of tyre combinations
- carbon filters
- hydraulic oil drain
- flashing beacon
- block heater

Dealer: