



Since 1946  
tractor is z e t o r



PROXIMA

*OPEN STATION*

*Zetor*

65 ■ 75 ■ 85 ■ 95

[www.zetor.com](http://www.zetor.com)

# ZETOR PROXIMA OPEN STATION

MODEL	UNITS	65	75	85	95
<b>ENGINE</b>					
Model		Zetor 7205	Zetor 1105	Zetor 1205	Zetor 1005
Homologated power 2000/25	kW/HP	47,6/65	56,3/77	64,3/87	70,4/96
Rated speed	rpm	2200			
No. of cylinders		4			
Aspiration		turbocharged			
Bore/Stroke	mm	105/120			
Displacement	cc	4156			
Torque reserve	%	36	37	35	35
Emissions		TIER III			
<b>CLUTCH</b>					
Type		dry, dual-purpose, hydraulic control			
Diameter	mm	310			
Lining		cerametallic			
<b>TRANSMISSION</b>					
Type		mechanical			
Shifting		fully synchronised			
Gears forward/reverse		standard 10/2			
Optional		synchronised shuttle 12/12, creeper 20/4, overdrive 20/4			
Speed	kmph	30			
<b>PTO SHAFT</b>					
Type		independent, ground speed PTO standard			
Speeds	rp	540, 540/1000 optional			
<b>HYDRAULICS</b>					
Type		mechanical, top link draft sensing			
Three point linkage		category I and II			
Control		position, draft, mixed			
Lift capacity	kN	32	40	40	40
Operating pressure	MPa	18			
Pump capacity	(l/min)	40	50	50	50
SCV's		one set of remotes standard			
<b>OTHER</b>					
Drive system		2WD/4WD			
Operator's station		open station with safety frame			
Steering		hydrostatic			
Service brake		wet disc brake, hydraulic control			
Parking brake		mechanical control			
Front axle 2WD		2° tilting			
Front axle 4WD		55° turning angle, limited slip front differential			
Rear axle		drop axle design, differential lock (engaged mechanically)			
<b>DIMENSIONS</b>					
Lenght	mm	3875			
Width	mm	1910			
Maximum height up to the safety frame top	mm	2758/2770			
Wheel base 2WD/4WD	mm	2321/2236			
Ground clearance 2WD/4WD	mm	490/402			
Standard front tyres		7,50-16/11,2-24			
Standard rear tyres		16.9-28	16.9-28	16.9-30	16.9-30
Weight 2WD/4WD	kg	2915/3225			
<b>OPTIONAL</b>					

- adjustable steering wheel ■ adjustable trailer hitch ■ pick-up hitch ■ front and rear weights ■ hydraulic trailer brakes ■ choice of tyre combinations
- canopy ■ flashing beacon ■ engine with emission stage TIER II



Dealer: